

The Marantz MM-9000 Five Channel Amplifier Provides Pure THX® Power to Spare.



Specifications

Amplifier Section

Continuous power output (RMS) into 8 ohms ($<.03\%$ THD, 20 Hz - 20 kHz)	
Front left and right channels	150 + 150 W
Center channel	150 W
Surround channels	150 + 150 W
Input sensitivity	100 mV/1 W Output
Input impedance	20 k Ω
Frequency response (-1 dB)	5 Hz to 100 kHz
Signal to noise ratio	95 dB

General

Power requirements	120 V, 60 Hz, 400 W
Dimensions W/H/D	17 $\frac{1}{16}$ " x 6 $\frac{1}{16}$ " x 7 $\frac{1}{8}$ "
	159mm x 440mm x 452mm
Weight	44.1 lbs. 20 kg.

The Marantz MM-9000 THX Ultra® certified multi-channel power amplifier is ideal for use in home theater systems wherever high power output is desired. Its 150 watts x 5 power output makes it especially suited to meet the sonic demands of Dolby Digital® and DTS® discrete 5.1-channel soundtracks.

MM-9000 Features:

150 watts x 5 channel power output (into 8 ohms), featuring fully discrete output topology with high-current output transistors. The MM-9000 can drive even difficult loudspeaker loads with ease.

Oversized power supply featuring a massive toroidal transformer and high-capacity electrolytic capacitors, for generous power reserves even when reproducing demanding action movie soundtracks at high volumes.

Premium-quality internal components used throughout for maximum signal purity. The MM-9000 reproduces movie soundtracks and surround sound music discs with extraordinary clarity, resolution and dynamic range.

THX Ultra® certified—the highest level of THX certification available, given only to audio/video components that meet the very highest standards of performance and sound quality.

Individual input level controls for each channel allow precise adjustment of each channel's volume level in multi-channel installations.

Smart Power On feature automatically turns the MM-9000 on whenever the TV or projector is turned on. The amplifier can also be turned on via a DC trigger signal or remote control.

D-BUS remote connection allows linkage to other Marantz components for integrated system operation.

Peak level indicators for each channel provide ready indication of clipping to guard against amplifier overload, should it ever occur.

Banana plug-compatible speaker terminals facilitate the use of high-quality speaker cables.

AC convenience outlet makes it easy to hook up an additional components.



"DOLBY", "DOLBY DIGITAL", "Dolby Pro Logic" and the double-D symbol are trademarks of Dolby Laboratories Licensing Corporation.

DTS is a registered trademark of DTS Technology.

THX and THX Ultra are registered trademarks of Lucasfilm Ltd.

All specifications are subject to change without notice.

© 1999 Marantz America, Inc.

marantz®

Marantz America, Inc. 440 Medinah Road Roselle, IL 60172

Phone 630-307-3100 • Fax 630-307-2687 • www.marantz.com

Download from www.Somanuals.com. All Manuals Search And Download.

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>