

PXC 310/PXC 310 BT

Noise Cancelling Headphones

Frequent travelers can finally have it all: aggressive noise cancelling, compact size, high-fidelity audio and options to listen wirelessly. Featuring NoiseGard™ 2.0 technology, the PXC 310 and PXC 310 BT reduce up to 90% of ambient noise and offer a convenient TalkThrough function. Perfect for your next adventure in the skies.



PXC 310

- Reduces up to 90% of ambient noise
- TalkThrough function permits chatting with seatmates without removing the headphones
- Collapsible, metal-reinforced headband with simple folding mechanism
- Intelligent, easy-to-use operating interface
- Neodymium magnets and Duofol diaphragms provide high-fidelity sound reproduction
- Optimized for in-flight entertainment systems (aircraft adapters included) and portable media devices
- Extensive accessories included: in-flight adapters, multi-country recharger, rechargeable Lithium-Polymer battery and carrying case

PXC 310 BT

- Same specifications as the PXC 310
- Bluetooth® 2.1 digital wireless reception technology (listen only) – compatible with countless Bluetooth enabled digital audio devices
- Supports apt-X®: sophisticated audio compression technology for true hi-fi quality
- Sennheiser BTD 300 Bluetooth dongles provide apt-X and Bluetooth audio transmission on-demand (sold separately)
- Works as a wired headphone without NoiseGard or Bluetooth activated



PXC 310



PXC 310 BT

The Bluetooth® word mark and logo are registered trademarks and are owned by the Bluetooth SIG, Inc. apt-x and the apt-x logo are trademarks or registered trademarks of APT Ltd.



Specifications

| Model | PXC 310 | PXC 310 BT |
|---------------------------------------|--|---------------|
| EAN No. | 4044156027302 | 4044156027289 |
| UPC No. | 615104140165 | 615104140141 |
| Cat. No. | 502386 | 502384 |
| Design | Premium collapsible mini-headphones | |
| Transducer principle | Dynamic, closed | |
| Ear coupling | On-the-ear | |
| Frequency response | 15-22,000 Hz | |
| Nominal impedance active/passive | 590/100 Ω | |
| SPL | 107 dB SPL | |
| THD at 1 kHz | < 0.1% | |
| Operating time NoiseGard | \leq 20 hrs | \leq 20 hrs |
| Operating time Bluetooth® | | \leq 12 hrs |
| Operating time Bluetooth® + NoiseGard | | \leq 8 hrs |
| NoiseGard active noise reduction | 23 dB | |
| Passive noise attenuation | 25 dB | |
| Weight | 3.7 ounces | |
| Cable length | | |
| Audio cable | 4.6 ft | |
| Charging cable | 3.9 ft (USB) | |
| Audio connector | 1/8" (3.5 mm) stereo jack plug | |
| Inflight adapters | 1/8" (3.5 mm) double mono jack plug, 1/4" (6.3 mm) stereo jack plug | |
| Bluetooth® | Version 2.1+ EDR | |
| Range | up to 33 ft. | |
| Protocols | A2DP, AVRCP | |
| Codec | SBC, apt-X | |
| Packaging | | |
| Design | Reclosable window cardboard box | |
| Packaging dimensions (W x H x D) | 7.5 x 3.3 x 7.9 inches | |
| Master carton dimensions (W x H x D) | 18.5 x 17.7 x 9.3 inches | |
| Units per master carton | 10 units | |
| Languages | German, English, French, Spanish, Italian, Dutch, Portuguese | |
| Delivery includes | Detachable audio cable (2.5 mm to 3.5 mm jack plug), in-flight audio adapter (3.5 mm double mono jack), 1/4" (6.3 mm) audio adapter, USB charging cable, multi-country wall charging adapter, rechargeable Lithium Polymer battery (BA 370), carrying case | |

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>