

General Description

Professional cardioid vocal microphone developed to cut through high on-stage levels. Rugged, durable construction, insensitive to handling noise. The e 840 efficiently suppresses sounds emanating from outside its pick-up angle, and is fitted with a hum compensating coil for reducing electromagnetic interference. Also available as e 840 S with noiseless on/off switch.


Technical Data

Pick-up pattern	cardioid
Frequency response	40 – 18,000 Hz
Sensitivity	
(free field, no load, 1 kHz)	2mV/Pa at 1 kHz = -54 dB
	(0 dB = 1V/Pa) = -74 dB
	(0 dB = 1V/μbar)
Nominal impedance	350 Ω
Min. terminating impedance	1 kΩ
Dimensions	47 x 181 mm
Weight	330 g

Features

- Rugged metal housing
- Shock-mount capsule
- Frequency-independent directivity
- Highly insensitive to feedback
- Excellent vocal projection
- Hum compensating coil
- Delivery includes protective pouch and MZQ 800 microphone clip
- Delivery includes: e 840, operating instructions, MZQ 800 microphone clip, protective pouch, guarantee card

Profile

Cardioid vocal microphone, hum compensating coil, frequency response 40 – 18,000 Hz, sensitivity (free field, no load) 2 mV/Pa at 1 kHz = -54dB (0 dB = 1V/Pa) = -74 dB (0 dB = 1V/μbar), nominal impedance 350 Ω, min. terminating impedance 1 kΩ, dimensions 47 x 181 mm, weight 330 g.

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>