

# SDC 3000 PS 25

Conference and Information Systems | SDC 3000

Cat. No. 004881

## General Description

The SDC PS 25 power supply unit powers up to 25 SDC 3000 D or SDC 3000 DC conference terminals. It is required for conference systems with more than 25 terminals (up to 25 terminals are powered directly by the SDC CU central unit). The SDC PS 25 can be connected anywhere in a cable string. The SDC PS 25 is supplied with a European IEC mains cable.



## Technical Data

Output voltage (conference bus).....	33 V
Output current (max.) (conference bus).....	3.2 A
Mains voltage .....	100 – 240 V (50 – 60Hz)
Max. power consumption.....	200 VA
Temperature range.....	+5 to + 50 °C
Max. humidity.....	95 %
Fan noise .....	37 dB(A)
Dimensions .....	242 x 96 x 375 mm
Weight .....	2.8 kg

## Recommended Accessories

- Mains cable, UK version – 230 V
- Mains cable, USA version – 120 V

Cat. No. 057256

Cat. No. 054325

## Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>