



Nuvera Digital Copier/Printer

The Nuvera 100/120 Digital Copier/Printer provides the power to produce the complex jobs your customers demand, the economics to keep you up and running every day, and the productivity to center your business around—now and as it continues to grow.

The right choice... for your budget,
for your needs, for your business

Xerox® Nuvera™ 100/120 Digital Copier/Printer

For more information on the Xerox Nuvera Digital Copier/Printer, call **1-800 ASK XEROX** or visit us on the Web at: www.xerox.com

Specifications

Document Scanning

Scan Rate

Speed based on 8.5" x 11"/A4-sized media:

- One sided: 120 images per minute
- Two sided: 120 images per minute (Dual scan heads)

Resolution

- Optical 600 x 600 dpi 8-bit Gray (256 shades) scan
- Maximum scan from platen: 12.0" x 18.0" (305 mm x 457 mm)
- Scan to File resolution: 300, 400, 600, 1200 dpi

Automatic Document Feeder

- Capacity: 300 sheets (20 lb bond/75 gsm)
- Sizes: 5.5" x 8.5" to 11" x 17" (A5 to A3)
- Weights: 13 lb bond – 80 lb cover (49 – 220 gsm)

Copy/Print Controller

RIP

Xerox Document Services Platform (FreeFlow® DocuSP®)

- 2.0 GHz, 1 GB RAM, 160 GB SATA Hard Drive
- DVD/CD-RW Drive
- 10/100/1000 Megabit Ethernet Port
- 4 USB v2.0 Port (two are used for Keyboard and Mouse)
- 15" LCD display, USB keyboard, mouse
- Page Description Languages (PDLs): Adobe PostScript® Level 3, PDF, PCL6, TIFF, Multi-page TIFF, ASCII
- Optional connectivity:
 - Ethernet interface (10/100BaseT)
 - Network connectivity: TCP/IP, LPR, IPP, HTTP, Novell® (SPX/IPX), AppleTalk®, SNMP

Storage

- Memory: 1 GB
- Hard Drives: 80 GB IDE Hard Drive/146 GB (optional second hard drive)
- CD-RW / DVD-ROM Drive

Print Submission Drivers

- Microsoft Windows® 95 through Windows® XP Professional
- Apple Macintosh® OS 8 through Macintosh® OS X
- Sun Microsystems™ Solaris™ 2.6, 7.x, 8.x, 9.0, 10.0
- Linux 2.x
- Xerox Web User Interface
- Xerox FreeFlow® Print Manager

Management Tool Support

- IBM® Tivoli®
- CA® Unicenter®
- HP OpenView
- SNMP V.1, IETF & Xerox MIB's, Trap Support
- CentreWare® Web

Printer Module

Image Quality

- Up to 1200 x 1200 dpi RIP resolution
- 4800 x 600 dpi print resolution
- Halftone screen: 125 lpi

Print Speed

- Nuvera 100 Digital Copier/Printer:
 - 8.5" x 11"/A4-sized media: 100 images per minute
 - 11" x 17"/A3-sized media: 60 images per minute
- Nuvera 120 Digital Copier/Printer:
 - 8.5" x 11"/A4-sized media: 120 images per minute
 - 11" x 17"/A3-sized media: 72 images per minute
- Warm-up: 4 minutes, 45 seconds
- Average Monthly Print Volume (AMPV):
 - Nuvera 100 Digital Copier/Printer: 60K – 400K per month
 - Nuvera 120 Digital Copier/Printer: 100K – 500K per month
- Duty Cycle:
 - Nuvera 100 Digital Copier/Printer: 600K per month
 - Nuvera 120 Digital Copier/Printer: 700K per month

Media Input Options

Input Capacity

- Feed Modules: maximum of 2 modules; 4 trays per module
 - Post-Process Inserter (optional)¹
 - Total 5,800 sheets per module (20 lb bond/75 gsm)
 - Air shuttle feed system
 - Optional two-tray high capacity feeder
- Capacity based on 20 lb bond/75 gsm:**
- Tray 1: 1,600 sheets; 5.5" x 8.0" to 9" x 12.6" (140 mm x 203 mm to 229 mm x 320 mm)
 - Tray 2: 3,100 sheets; 5.5" x 8.0" to 9" x 12.6" (140 mm x 203 mm to 229 mm x 320 mm)
 - Tray 3 and 4: 550 sheets each; 7.2" x 8.0" to 12.6" x 18.5" (183 mm x 257 mm to 320 mm x 470 mm)

Media Latitude

- Sizes: 5.5" x 8.0" to 12.6" x 18.5" (140 mm x 216 mm to 320 mm x 470 mm)
- Weights: 16 lb bond to 80 lb cover (56 – 220 gsm)
- Paper Types:
 - Uncoated: bond, Bristol, cover, index, offset, recycled and more
 - Specialty¹: transparencies, Never Tear, DuraPaper®, carbonless, labels, tabs, preprinted forms and more

Foreign Device Interface

- 15 pin subminiature "D" connector
- Connects to a number of external charge-related devices
 - Coin box, magnetic card reader, alpha terminal

Media Output Options

Multifunction Finisher Standard

Capacity based on 20 lb bond/75 gsm:

- Top tray: 250 sheet capacity
- Stacker: 2,000 sheet capacity; offset between sets or jobs
- One or two staples, up to 100 sheets

Multifunction Finisher Professional

All standard features listed above plus:

- 8.5" x 11"/A4 sheet inline folder (C-type, Z-type, booklet/bi-fold)
- 11" x 17"/A3 sheet inline folder (booklet/bi-fold)
- 15 sheet (60 page) dual staple booklet maker

Electrical Requirements

Standard configuration: one Feed Module with Finisher¹

- 208 – 240 VAC, 30 amp wall service
- Optional AC adapter box, 50 amps
- Power consumption: 0.723 kw (standby); 4.275 kw (running)

Environmental Requirements

- Temperature: 50° to 90° F (10° to 32° C)
- Relative Humidity: 15 to 85%
- Run Mode Heat Emissions: 17,537 BTUs/hr

Certifications

- ENERGY STAR
- Section 508 of the Rehabilitation Act
- UL 60950, third edition, CSA 22.2 no. 950 & ICES-003-2 B and IEC 60950, third edition

Physical Characteristics

Standard configuration: one Feed Module with Finisher

Width	Depth	Height	Weight
131"	30"	61.6"	1,753 lbs ¹
3336 mm	736 mm	1565 mm	795 kg ¹

Additional Modules available¹

Service access requirements:

	Width	Depth
Moveable	162"	92" ¹
	4114.8 mm	2336.8 mm
Stationary	162"	113"
	4114.8 mm	2870 mm

Xerox FreeFlow® Digital Suite of Solutions offers a host of Xerox and partner products that aid in streamlining workflow in any print environment. Visit <http://www.xerox.com/workflow> for more information.



¹ Consult Xerox for unique specification parameters

©2006 XEROX Corporation. All rights reserved. XEROX®, DocuSP®, easy-vi™, FreeFlow® and Nuvera™ are trademarks of Xerox Corporation in the U.S. and/or other countries. Product appearance, build status and/or specifications are subject to change without notice. The Xerox Total Satisfaction Guarantee applies to equipment under a Xerox warranty or a Full Service Maintenance Agreement and is subject to certain conditions. Solaris™ is a trademark of Sun Microsystems™. Windows® is a registered trademark of Microsoft Corporation. AppleTalk® and Macintosh® are registered trademarks of Apple Computer, Inc. Tivoli® is a registered trademark of IBM, Inc. Unicenter® is a registered trademark of Computer Associates, Inc. Adobe® and PostScript® are registered trademarks of Adobe Systems, Inc. Novell® is a registered trademark of Novell, Inc. ENERGY STAR® and the ENERGY STAR mark are registered U.S. marks. As an ENERGY STAR partner, Xerox Corporation has determined that this product meets the ENERGY STAR guidelines for energy efficiency. Terra Choice Environmental Services of Canada has verified that this Xerox product conforms to all applicable Environmental Choice Ecologo requirements for minimal impact to the environment. 8/06. 610P716870C

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>