

PRODUCT: Document Centre 332DC/332ST/340DC/340ST
 Document Centre 425DC/425ST
 Document Centre 432DC/432ST/440DC/440ST

PSDS No.: 0823
ISSUE DATE: 07/30/99
REV. DATE: 06/18/01

Section I - Product Identification

Manufacturer's Name
 Xerox Corporation

Emergency No. EH&S Inquiries
 (585) 422-2177 (800) 828-6571

Manufacturer's Address
 Rochester, New York 14644

Product Designation
 Document Centre 332DC/332ST/340DC/340ST
 Document Centre 425DC/425ST
 Document Centre 432DC/432ST/440DC/440ST

Product Identifier
 XTC-1

Section II - Electrical Information

Line Voltage (Volts)	Line Current (Amps)	Freq. (Hertz)
115-127	10	60

Branch Cir. Protection
 (Amps)
 15

Line Cord/Plug Specification
 Equipped with Appliance Coupler
 Detachable Cord, Two wire + Ground
 NEMA 5-20R

Power Consumption(Watts)*
 Running: 750
 Standby: 200
 Low Power: 100

Agency Approval
 UL File Number E51370

Section III - Supplies

	Xerox Part No.
Dry Ink, CRU	113R316, 113R317, 113R321 113R322, 113R323, 113R324

Material Safety Data Sheet
 A-0600

Section IV - Environmental Information

Floor Space Requirements
 (Meters)
 W: 2.27
 D: 1.83

Heat Emission*
 Running: 2,550
 Standby: 680

Environmental Limitations

	<u>Min</u>	<u>Max</u>
Relative Humidity (%)	10	85
Ambient Temp. (°C)	10	32

Product Size
 Centimeters
 D: 55.4
 W: 65.5 or 128.5 with DSS/HCF
 H: 109.4 or 128.0 with TMB

Weight
 (K Grams)
 IOT & IIT 120
 DSS 19
 HCF 18
 TMB 16

* Based on a five minute average

** MSDS is not required by OSHA, Hazard Communication Std., 29 CFR or WHMIS HPA (Section II (2))

Product: Document Centre 332DC/332ST/340DC/340ST
Document Centre 425DC/425ST
Document Centre 432DC/432ST/440DC/440ST

PSDS No.: 0823

Section V - Emission/Exposure Information*

Light Source

FDA registered Class 1 Laser Product
(Internal Helium Neon Laser)
Fluorescent Scanner Lamp

FDA Accession

9720281-02

Electromagnetic Emissions

US FCC: Class A
Canada DOC: Class A

Audible Noise

	Base Machine
Power Saver:	47.0 dB(A)
Standby:	50.0 dB(A)
Run:	64.0 dB(A)
Impulse:	69.0 dB(A)

TLV

	Base Machine with DSS and HCF
	85.0 dB(A)
	47.0 dB(A)
	40.0 dB(A)
	70.0 dB(A)
	75.0 dB(A)

Ozone

68 ug/min
0.009 ppm (TWA)

TLV

0.1 ppm

Concentration Based on Customer Simulation Model:
Daily Copy Volume 3,000 copies/8 hours
Room Size 9 m³
1/2 Air Room Change per Hour

Total Dust

Not Detected mg/m³

TLV

10 mg/m³

Section VI - Product Recycling and Disposal

This product may contain lead, mercury and other materials whose disposal may be regulated due to environmental considerations. For recycling and disposal information, contact your local authorities. In the United States, you may also refer to the Electronic Industries Alliance web site: www.eiae.org. For information on Xerox's worldwide equipment return and recycling programs, visit www.xerox.com (refer to "About Xerox" section).

* TLV (Threshold Limit Value) and PEL (Permissible Exposure Level) respectively set by American Conference of Government Industrial Hygienists and by Occupational Safety and Health Administration. These levels are considered maximum exposure permitted to ensure no health hazard. TWA (Time Weighted Average) for normal, eight-hour workday.

All measurements were made on products performing within established operating specifications and received recommended maintenance procedures. Xerox certifies that this product meets or exceeds the applicable standards for safety and emissions.

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>