



FMM-325A Series Analog Manual Stations



- ▶ **Compatible with advanced digital communication protocol**
- ▶ **Digital data communications and power provided over two-wire circuit**
- ▶ **EEPROM addressing in module unit**
- ▶ **Rugged die-cast housing and corrosion resistant construction**
- ▶ **Single-gang mounting**
- ▶ **Latching alarm lever**
- ▶ **UL listed for commercial fire applications**
- ▶ **Meets Americans with Disabilities Act (ADA) requirements**

The FMM-325A Series Analog Manual Stations are used in the polling circuit of the Bosch Security Systems, Inc.'s FPA-1000-UL, D9024, D8024, and D10024A Fire Alarm Control Panels (FACP). They communicate with the control panel (both power and data) over a two-wire polling circuit.

The manual station's address on the polling circuit is set by programming an EEPROM microchip. The D5070 Analog Device Programmer is required to set the address.

All commercial buildings use manual stations. These manual stations allow people evacuating a building to initiate an alarm. The FACP identifies the alarm point on the polling circuit and the alarm lever latches in the pulled position.

Installation/Configuration Notes

Compatibility Information

The following products are compatible with the FMM-325A Series Analog Manual Stations:

| Category | Product ID | Product Description |
|-----------------|-------------|--------------------------|
| Control Panels: | FPA-1000-UL | Compact Fire Panel |
| | D8024 | Analog FACP |
| | D9024 | Analog FACP |
| | D10024A | Analog FACP |
| Programmers: | D5070 | Analog device programmer |

Mounting Considerations

The FMM-325A manual stations are for indoor use only.

The FMM-325A Series Analog Manual Stations have die-cast housings that flush mount on a single-gang back box. For surface mounting, use an FMM-100BB-R Surface-mount Back Box.

Certifications and Approvals

| Region | Certification | |
|--------|---------------|--|
| USA | UL | UNIU: Boxes, Non-Coded (UL38) |
| | CSFM | 7150-1615: 122 |
| | ADA | Complies with Americans with Disabilities Act ADA 4.28.3 |
| | NFPA | Complies with National Fire Protection Association NFPA 72 |

Parts Included

| Quant. | Component |
|--------|-----------------------------------|
| 1 | Manual station |
| 1 | Point Contact Module |
| 1 | FMM-100GR Scored Acrylic Breakrod |
| 1 | D102 Key (#1358) |
| 1 | Literature pack |

Technical Specifications**Electrical****Current**

| | |
|----------|-----------------|
| Alarm: | 28 mA |
| Polling: | 22 mA ± 20% |
| Standby: | 0.35 mA typical |

Voltage

| | |
|------------|------------------|
| Input: | 24 VDC nominal |
| Operating: | 17 VDC to 41 VDC |

Environmental Considerations

| | |
|--------------------------|-------------------------------------|
| Temperature (operating): | +14°F to +120°F (-10°C to +49°C) |
|--------------------------|-------------------------------------|

Mechanical Properties

| | |
|-------------------------|---|
| Activation Force: | 5 lb (2.3 kg) |
| Dimensions (H x W x D): | 4.75 in. x 3.2 in. x 0.875 in. (12.1 cm x 8.1 cm x 2.2 cm) |
| Material: | Painted die-cast metal |

Ordering Information

| | |
|---|-----------------|
| FMM-325A Single-action Manual Station Communicates with the FPA-1000-UL, D9024, D8024, and D10024A FACP's (both power and data) over a two-wire polling circuit | FMM-325A |
|---|-----------------|

| | |
|---|-------------------|
| FMM-325A-D Double-action Manual Station Communicates with the FPA-1000-UL, D9024, D8024, and D10024A FACP's (both power and data) over a two-wire polling circuit | FMM-325A-D |
|---|-------------------|

Accessories

| | |
|---|-------------|
| D102 Replacement Key Replacement key (#1358) for the D101 lock. | D102 |
|---|-------------|

| | |
|--|--------------------|
| FMM-100BB-R Surface-mount Back Box (red) Red cast-metal back box | FMM-100BB-R |
|--|--------------------|

| | |
|--|------------------|
| FMM-100GR Scored Acrylic Break Rods Scored acrylic rods (12 per package) | FMM-100GR |
|--|------------------|

Americas:
Bosch Security Systems, Inc.
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
security.sales@us.bosch.com
www.boschsecurity.us

Europe, Middle East, Africa:
Bosch Security Systems B.V.
P.O. Box 80002
5600 JB Eindhoven, The Netherlands
Phone: +31 40 2577 284
Fax: +31 40 2577 330
emea.securitysystems@bosch.com
www.boschsecurity.com

Asia-Pacific:
Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6258 5511
Fax: +65 6571 2698
apr.securitysystems@bosch.com
www.boschsecurity.com

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>