

CW-L300

User's Guide

- We recommend that you print on a disc* before you record anything on it. Printing on a disc that already has data recorded on it can cause the data to become corrupted.
- Note that CASIO COMPUTER CO., LTD. shall not be held liable for any loss or corruption of data on discs arising through the use of this printer.

* CD-R, CD-RW, DVD-R, etc.

Be sure to read the Safety Precautions contained in this manual before trying to use the printer for the first time, and always keep this manual on hand for future reference.

RJA514733-10

CASIO[®]

GUIDELINES LAID DOWN BY FCC RULES FOR USE OF THE UNIT IN THE U.S.A. (not applicable to other areas).

NOTICE

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

Caution: Changes or modification to the product not expressly approved by CASIO could void the user's authority to operate the product.

FCC WARNING

Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

Proper connectors must be used for connection to host computer and/or peripherals in order to meet FCC emission limits.

Cable specified for PC Windows® compatible PC to CW-L300

Declaration of Conformity

Model Number: CW-L300

Trade Name: CASIO COMPUTER CO., LTD.

Responsible party: CASIO, INC.

Address: 570 MT.PLEASANT AVENUE, DOVER, NEW JERSEY 07801

Telephone number: 201-361-5400

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Read This First!

- CASIO COMPUTER CO., LTD. shall not be held liable for any loss or claims by you or any other person or entity that may arise through the use of this printer.
 - Reproduction of this manual in any form, either in part or its entirety, is forbidden without the express permission of CASIO COMPUTER CO., LTD.
 - The contents of the manual are subject to change without notice.

 - Windows is a registered trademark of Microsoft Corporation in the United States and other countries.
 - Other company and product names used herein may also be company and product names of others.
- © Copyright 2004 CASIO COMPUTER CO., LTD. All rights reserved.
- Be sure to read this manual carefully before attempting to use the product for the first time.

Safety Precautions

Thank you for purchasing this quality CASIO product. Before using it, be sure to read the following Safety Precautions. Keep the manual in a convenient location for future reference when necessary.



Danger

This symbol indicates information that, if ignored or applied incorrectly, creates the danger of death or serious personal injury.



Warning

This symbol indicates information that, if ignored or applied incorrectly, creates the possibility of death or serious personal injury.




Caution


This symbol indicates information that, if ignored or applied incorrectly, creates the possibility of personal injury or material damage.

Examples of graphic markings



 indicates something you should not do. The symbol shown here indicates you should not try to take the unit apart.



 indicates something you should do. The symbol shown here indicates you should unplug the unit from the wall outlet.

Danger

Alkaline Batteries



Perform the following steps immediately if fluid leaking from alkaline batteries ever gets into your eyes.

1. Do not rub your eyes! Rinse them with water.
2. Contact your physician immediately.

Leaving alkaline battery fluid in your eyes can lead to loss of sight.

Warning

Smoke, abnormal odor, overheating, and other abnormalities



Continued use of the product while it is emitting smoke or strange odor, or overheating creates the risk of fire and electric shock. Immediately perform the following steps whenever any of the above symptoms are present.

1. Turn off power.
2. Unplug the power cord from the wall outlet.
3. Contact your original retailer.

Power cord, AC adaptor, USB cable



Misuse of the power cord, AC adaptor, or USB cable creates the risk of fire and electric shock.

Make sure you follow the precautions listed below.

- Use only items that are specified for the product.
- Use only a power source whose output matches the rating marked on the plate on the back of the product.
- Never plug the power cord into a wall outlet that is shared by other devices, or into a shared extension cord.



Warning

Power cord, AC adaptor, USB cable



Misuse of the power cord, AC adaptor, or USB cable can damage it and create the risk of fire and electric shock. Make sure you follow the precautions listed below.

- Never place heavy objects on these items or subject them to direct heat.
- Never modify these items or subject them to bending.
- Do not subject these items to twisting or pulling.
- Should the power cord, AC adaptor, or USB cable or its plug ever become damaged, contact your original retailer.



Power cord, AC adaptor, USB cable



Never touch the power cord, AC adaptor, or USB cable or its plugs while your hands are wet. Doing so creates the risk of electric shock.

- Never use the power cord or AC adaptor in areas where it may become wet. Water creates the risk of fire and electric shock.
- Never place a vase or any other liquid container on top of the power cord, AC adaptor, or USB cable. Water creates the risk of fire and electric shock.

Batteries



Misuse of batteries can cause them to leak, resulting in damage to nearby objects, or to explode, creating the risk of fire and personal injury. Always make sure you observe the following precautions.

- Never try to take batteries apart or allow them to become shorted.
- Never expose batteries to heat or dispose of them by incineration.
- Never mix old batteries with new ones.
- Never mix batteries of different types.
- Do not charge the batteries.
- Make sure the positive (+) and negative (–) ends of the batteries are facing correctly.



 **Warning**

Dropping and rough treatment



Continued use of the product after it has been damaged due to dropping or other rough treatment creates the risk of fire and electric shock. Immediately perform the following steps if the product should ever become damaged.

1. Turn off power.
2. Unplug the power cord from the wall outlet.
3. Contact your original retailer.

Do not disassemble or modify the product.



Never try to take the product apart or modify it in any way. Doing so creates the risk of electric shock, burn injury, or other personal injury. Leave all internal inspection, maintenance, and repair up to your original retailer.

Water and foreign objects



Water, liquids, or foreign objects (especially metal) getting inside the product creates the risk of fire and electric shock. Immediately perform the following steps if liquid or a foreign object should ever get inside the product.

1. Turn off power.
2. Unplug the power cord from the wall outlet.
3. Contact your original retailer.

Do not incinerate.



Never dispose of the product by incineration. Doing so creates the risk of fire and personal injury due to explosion.

Plastic bag precaution



Never place the plastic bags in which the product comes packed over your head. Doing so creates the risk of suffocation. Particular care is required in households where young children are present.

 **Warning**

Do not affix labels to a container to be used in a microwave oven.



Do not affix labels to any container you plan to use in a microwave range. The label material contains metal, which creates the risk of fire and burn injury when heated in a microwave oven. It can also cause deformation of the container to which the label is affixed.

 **Caution**

Power cord, AC adaptor, USB cable



Misuse of the power cord, AC adaptor, or USB cable can damage it and create the risk of fire and electric shock. Make sure you follow the precautions listed below.

- Never locate these items near a stove or other source of intense heat.
- When unplugging the power cord and USB cable, be sure to grasp the plug. Never pull on the cord or cable.
- Plug in the power cord into the wall outlet as far as it will go.
- Plug in the USB cable into the computer and the printer as far as it will go.
- Before leaving the product unattended for long periods (such as when you go on a trip), unplug the power cord and USB cable.
- At least once a year, clean away any dust built up in the area around the prongs of the power cord's plug.



Batteries

Misuse of batteries can cause them to leak resulting in damage to nearby objects, or to explode, creating the risk of fire and personal injury. Always make sure you observe the following precautions.



- Use only batteries that are specified for use with this product.
- Remove batteries from the product if you do not plan to use it for a long time.

Caution

Connection precaution



Connect only items that are specified for the product to its connectors. Connecting a non-specified item creates the risk of fire and electric shock.

Keep backup copies of all important data



Be sure that you keep separate copies of important data in a notebook or some other location. Malfunction of the product, repairs, and dead batteries can cause data stored memory to be lost.

Keep heavy objects off.



Never place a heavy object on top of the product. Doing so can cause the object to lose balance and fall, creating the risk of personal injury.

Location



Avoid the locations listed below for the product. Such locations create the risk of fire and electric shock.

- Areas subject to high humidity and large amounts of dust
- Food preparation areas or other location subjected to oil steam
- Near heaters, on a heated carpet, in direct sunlight, in a closed vehicle parked in the sun, and other areas subjected to high heat.

Avoid unstable surfaces.



Never place the product on an unstable table, desk, etc. Doing so can cause the product to fall, creating the risk of personal injury.

Caution

Loading and replacing batteries



The springs inside of the battery compartment have sharp edges. Take care that you do not touch the springs with your fingers when loading or replacing batteries. Doing so creates the risk of personal injury.

Display Screen



- Never push on the display screen's LCD panel or subject it to strong impact. Doing so can cause the LCD panel's glass to crack, creating the risk of personal injury.
- Should the LCD panel ever crack or break, never touch the liquid inside of the panel. LCD panel liquid can cause skin irritation.



- Should LCD panel liquid ever get inside your mouth, immediately wash out your mouth with water and contact your physician.
- Should LCD panel liquid ever get into your eyes or onto your skin, rinse with clear water for at least 15 minutes, and then contact a physician.

High temperature precaution



Never touch the print head or other metal objects near the head. These items become very hot, and touching them creates the risk of burn injury.

Auto Cutter



While the printer is turned on or printing, never touch the printer head or the area where the tape passes. Unexpected operation of the cutter creates the risk of personal injury.

Operating Precautions

Observe the following precautions to ensure that the printer provides you with the years of trouble-free operation for which it is designed.

- Avoid use in areas subjected to direct sunlight, high humidity, and temperature extremes. Operating Temperature Range: 10°C to 35°C (50°F to 95°F)
- Never allow paper clips, pins, or other similar objects to get inside the printer mechanism.
- Never pull on the tape with excessive force or try to push it into the cassette.
- Place the printer on a level surface when printing. A tilted surface can make normal printing impossible.
- Unclear printing can indicate a dirty print head. If printing becomes unclear, use the procedures on page 58 to clean the print head and rubber roller.
- Using the printer in an area that is exposed to direct sunlight or any other source of bright light can cause malfunction of its optical sensor, and display of an error message. Use the printer in an area that is not exposed to bright light.
- You cannot perform disc label printing and tape label printing at the same time.

Contents

Safety Precautions	1
Operating Precautions	5
Part 1 - DISC Mode	8
Disc Printing Terms	8
DISC Mode	8
Creating Disc Label Data	8
Creating a New Label	9
Inserting a Logo into a Label	11
Built In Logos	11
Output Samples	11
To insert a logo into a label	12
Inputting Text into an AUTO Format	12
To input text into an AUTO format label	12
Specifying Character Spacing	13
To turn proportional spacing on and off	13
Specifying Text Alignment	13
To specify text alignment	14
Printing Disc Case Labels	14
Creating and Printing a Disc Case Label	14
Part 2 - TAPE Mode	16
Creating a Tape Label	16
Creating and Printing a Sequentially Numbered Tape Label	17
Numbering Formats	17
Creating and Printing a Large Tape Label	19
Creating and Printing a Tape Label with a Logo	20
Built-in Logos	20

Creating and Printing an Original (Free Design) Tape Label	22
FREE DESIGN: Using Text Blocks	22
FREE DESIGN: Using Multiple Lines in a Tape Label	23
FREE DESIGN: Configuring Block Form Settings	25
FREE DESIGN: Configuring Label Form Settings	26
FREE DESIGN: Controlling the Length of a Tape Label ...	27
FREE DESIGN: Aligning Tape Label Text	29
Example 1: Aligning the term "Round Estimate①" in a block (fixed block length)	29
Example 2: Aligning blocks within a tape label	30
FREE DESIGN: Changing the Size of Tape Label Text	31
Specifying the Size of a String of Characters	31
Specifying the Size of Text Lines	33
FREE DESIGN: Using Frames	35
Creating a Barcode Tape Label	36
Supported Barcode Types	36
Barcode Specifications	37
Using Tape Labels	38
Tape Cut Modes	38
Types of Tape Cuts	38
Cut Modes	38
Cut Modes and Margins	40
Part 3 - Inputting and Editing Label Text	41
Moving the Cursor	41
Basic Alpha Numeric Input	41
To input alpha-numeric characters	41
About the CODE key	42
Inputting Symbols and Special Characters	42
To use the SYMBOL menu	42
Inputting Illustrations	43
To input illustrations	43

Deleting an Individual Character	43
To delete a character using the BS key	43
To delete a character using the DEL key	43
Clearing Input Text	44
To clear all text	44
To delete a range of text (Free Design)	44
Text Editing	44
To switch between overwrite and insert	44
Using Phrase Memory	45
To recall a phrase	45
To create new phrase memory text	45
To save input text in phrase memory	45
To edit a phrase memory record	46
To delete a phrase memory record	46
Using Copy and Paste	47
User Characters	47
To recall a user character	49
To delete a user character	49
Part 4 - Controlling the Appearance of Text	50
Selecting a Font	50
SMALL FONT	50
To change the default font setting	51
To change the font of text you have just input	51
Using STYLE Menu Attributes	52
Using EFFECT Menu Attributes	53
Part 5 - Saving, Recalling and Deleting Labels	54
To save a label	54
To recall a label	54
To delete a label	54

Part 6 - Configuring the Printer Setup	55
Demo Printing	55
Reference	57
Power Requirements	57
Caring for the Printer	58
Troubleshooting	59
DISC Mode	60
TAPE Mode	61
Error Messages	63
Illustrations	68
Symbols, Dingbats, and Special Characters	68
Frames	69
Disc Label Formats	70
Numbering Formats	71
Tape Width and the Number of Lines and Character Sizes ..	72
Supported Tape Widths	72
Enlarged Label Printing Tape Widths and Character Sizes ..	73
Specifications	74

Part 1 - DISC Mode

Disc Printing Terms


The following defines a few disc printing terms that are used in this part of the manual.

■ Print Surface

This is the side of the disc that the printer will print on. Some discs may have manufacturer logos or other information pre-printed on this side.


■ Print Data

This is the text, illustrations, and all other items that the printer will print onto the print surface of the disc.



■ Print Areas

These are the areas on the disc where the printer prints. The printer can print in two print areas: an upper print area and a lower printer area.



DISC Mode

Creating Disc Label Data

The following are the general steps when preparing data for disc labeling. After inputting the required data, you can then use it to print directly onto the disc, or for output on a tape that you can affix to the disc case.

Getting Ready

- Connect the AC adaptor or load batteries (page 7 of the Startup Guide).
- Load an ink ribbon cassette (page 11 of the Startup Guide).
- If you plan to print a disc case label, load a tape cartridge (page 13 of the Startup Guide).

General Flow for Creating a Disc Label

Select the DISC Mode (page 9).

1. To create a new label from scratch, select **NEW** on the initial screen (page 9).

To edit an existing label, select **STORED DATA** (page 54).

To edit the label data you were working on the last time you were using the printer, select **LAST DATA** (page 10 of the Startup Guide).

2. Select the print pattern you want to use (page 9).

3. Select the format you want to use (page 10).

4. Input the text you want (page 41).

5. Select the text attributes you want.

- Specify the font (page 50), select the style (page 52), and specify the text alignment (page 14).

Print the label (page 20 of the Startup Guide) and store it in memory (page 54), if you want.

Creating a New Label

This section explains how to specify the print area and select a label format for creating new disc printing data.


- For information about printing data that you have previously saved to memory, see page 54.

Example



■ To create a new disc label

- Press **ON** to turn on the printer.
 - A **LAST DATA** icon will also appear on the Main Menu if there is input data left over from the last time you used the printer. If you want to continue working with the data from your previous session, use **←** and **→** to select **LAST DATA**, and then press **SET**.
- Use **←** and **→** to select **DISC**, and then press **SET**.
 - You can also press **DISC** here.
- Use **←** and **→** to select **NEW**, and then press **SET**.
 - This displays a print pattern selection screen.
- Use the cursor keys to select the print pattern you want.



Print Pattern	AREA A AREA B	AREA A AREA B	 AREA B
	Example	 SPEECH CONTEST	 SPEECH CONTEST

5. Press **SET**.



Label format image

■ **Label Formats**

The label format determines the types and positions of text and logo data for each block. There are a total of 24 different formats, which are divided among three groups: standard formats (FORMAT 1 through FORMAT 18), logo formats (LOGO 1 through LOGO 4), and auto formats (AUTO 1 and AUTO 2).

If you want to do this:	Select this type of format:
Input text only	FORMAT 1 through FORMAT 18
Input text and a logo • See "Inserting a Logo Into a Label" on page 11 for information about inputting logos.	LOGO 1 through LOGO 4
Have the printer automatically select text size in accordance with the number of characters • See page 12 for more information.	AUTO 1 or AUTO 2

• See "Disc Label Formats" on page 70 for details about all the label formats that are available.

6. Use **◀** and **▶** to scroll through the available label formats until the one you want is displayed.




This is the currently selected label format.

7. Press **SET**.

- Note that if you selected **8** as the print pattern in step 4, pressing **SET** will display a screen for specifying the label format for the AREA B area. Repeat steps 6 and 7.
- Pressing **SET** causes the text input screen to appear.

8. Input the text you want.




Name of block where you are currently inputting text.

Block where you are inputting text flashes.

- See "Inputting and Editing Label Text" on page 41 for information about inputting text.

9. Press **SET**.



10. Repeat steps 8 and 9 for other blocks.

11. After all input is complete, press **SET**.

- This displays a screen, which you can use to print the label (page 20 of the Startup Guide) or to save the label (page 54).



- You can also exit your label making session by using the cursor keys to select **EXIT**, and then pressing **SET** twice.

Inserting a Logo Into a Label

When creating a label using a LOGO format (LOGO 1 through LOGO 4), you can insert one of the printer's 10 built-in logos into the graphic block of the format.

Built-in Logos



Output Samples

The following shows examples of labels that use logos.

LOGO 1



LOGO 2



LOGO 3



LOGO 4



To insert a logo into a label

1. Perform steps 1 through 5 of the procedure under "To create a new disc label" on page 9.
2. On the label format selection screen, use \leftarrow and \rightarrow to scroll through the label formats until one of the LOGO formats (LOGO 1 through LOGO 4) is displayed.
3. Press **SET**.
4. Use \leftarrow and \rightarrow to scroll through the logo data names, until the one you want is on the display.
5. Press **SET**.
 - This inserts the logo into the label. Now you can perform the other steps under "To create a new disc label" on page 9 to input text.

Inputting Text into an AUTO Format

The two AUTO formats automatically adjust the size of characters in accordance with the number of characters you input.

The table below shows how character size is adjusted for each auto format.

Number of Input Characters	AUTO 1 (1 line)		AUTO 2 (2 lines)	
	Displayed Size	Printed Size	Displayed Size	Printed Size
0 to 9	x5	15mm ($\frac{5}{8}$ "	x2	6mm ($\frac{1}{4}$ "
10 to 12	x4	12mm ($\frac{1}{2}$ "	x2	6mm ($\frac{1}{4}$ "
13 to 16	x3	9mm ($\frac{3}{8}$ "	x2	6mm ($\frac{1}{4}$ "
17 to 24	x2	6mm ($\frac{1}{4}$ "	x2	6mm ($\frac{1}{4}$ "
25 to 49	x1	3mm ($\frac{1}{8}$ "	x1	3mm ($\frac{1}{8}$ "


To input text into an AUTO format label

1. Perform steps 1 through 5 of the procedure under "To create a new disc label" on page 9.
2. On the label format selection screen, use \leftarrow and \rightarrow to scroll through the label formats until AUTO1 or AUTO2 is displayed.
3. Press **SET**.
4. Input the text you want.
5. Press **SET**.
 - Now you can perform the other steps under "To create a new disc label" on page 9 to complete the label.

Specifying Character Spacing


There are two ways that characters can be spaced: proportional spacing and uniform spacing.

With proportional spacing, the amount of space between two characters depends on what those two characters are.







ABC·XYZ

With uniform spacing, all characters are separated by the same amount of space.



A B C · X Y Z


To turn proportional spacing on and off

1. While inputting text, press **FORM**.
2. Use  and  to select **PROPORTIONAL**, and then press **SET**.
3. Use  and  to turn proportional spacing on or off.
 - Note that the setting you select is applied to all the text of the label.
4. Press **SET** to apply your setting and return to the text input screen.

Specifying Text Alignment

You can select any one of the following four text alignments for your label text.

Centering




ABC·XYZ

Right Alignment




ABC·XYZ

Left Alignment



ABC·XYZ

Equal Spacing



A B C · X Y Z

To specify text alignment

1. While inputting text, press **FORM**.
2. Use \uparrow and \downarrow to select **ALIGN**, and then press **SET**.
3. Use \leftarrow and \rightarrow to select the alignment setting you want.
4. When the setting you want is selected, press **SET**.
5. On the next screen that appears, use \uparrow and \downarrow to select the range of text to which you want to apply your alignment setting.

To apply the alignment setting to this text:	Select this option:
All of the text in the label	ALL
All of the text in the current line only	LINE

6. After selecting the range, press **SET** to apply your setting and return to the text input screen.

Printing Disc Case Labels

Use the procedures in this section to print a tape label that can be affixed to the case of a disc.

Creating and Printing a Disc Case Label

Important!

- When printing a disc case label, use 24mm or 18mm wide tape only.



■ To print a disc case label


1. Press **ON** to turn on the printer.
2. Use the procedures under "Creating Disc Label Data" on page 8 to prepare the data you want to print.
3. Pressing **SET** in step 11 of the procedure under "To create a new disc label" on page 10 will cause the screen shown below to appear.



4. Use \leftarrow and \rightarrow to select **PRINT**, and then press **SET**.
5. Use \leftarrow and \rightarrow to select **TAPE**, and then press **SET**.
 - Pressing \leftarrow and \rightarrow toggles the selection on the above screen between **DISC** and **TAPE**.
6. Use \leftarrow and \rightarrow to select the label area data you want to print first, and then press **SET**.

To print this data:	Select this option:
Upper label area	AREA A
Lower label area	AREA B

- The above step is not necessary if your label has data in only one of the label areas. In this case, go directly to step 7.
 - Here we will select **AREA A**.
7. Use the number keys (or \leftarrow and \rightarrow) to specify the number of copies, and then press \downarrow .
 - You can specify a value from 1 to 100 for the number of copies.
 8. Use \leftarrow and \rightarrow to select the tape cut mode (page 38), and then press **SET**.
 9. When printing is complete, the screen shown below will appear on the display.



- The above display will not appear if your label has data in only one of the label areas. In this case, skip steps 10 and 11, and go directly to step 12.

10. Use \leftarrow and \rightarrow to select the label area data you want to print next, and then press **SET**.
 - Here we will select **AREA B**.
11. Repeat steps 7 through 9 above to print in the other label area.
12. The following screen will appear when printing is complete.



13. Press \leftarrow and \downarrow to select **EXIT**, and then press **SET**.
 - Use **STORE** if you want to save the data. See page 54 for more information.



14. Press **SET** to exit the print operation.

Part 2 - TAPE Mode

Creating a Tape Label

The following are the general steps when preparing data for printing a tape label.

Getting Ready

- Connect the AC adaptor or load batteries (page 7 of the Startup Guide).
- Load a tape cartridge (page 13 of the Startup Guide).

Select the TAPE Mode (page 16).

1. Select the label mode.

Free Designpage 22
Numbering Label ...page 17
Barcode Labelpage 36
Enlarged Labelpage 19
Logo Labelpage 20

To edit an existing label, select **STORED DATA** (page 54).

To edit the label data you were working on the last time you were using the printer, select **LAST DATA** (page 10 of the Startup Guide).

2. Input the text you want (page 41).

3. Select the font (page 50) and the style (page 52).

Print the label (page 23 of the Startup Guide) and store it in memory (page 54), if you want.

■ To create a new tape label

1. Press **ON** to turn on the printer.
 - A **LAST DATA** icon will also appear on the Main Menu if there is input data left over from the last time you used the printer. If you want to continue working with the data from your previous session, use **←** and **→** to select **LAST DATA**, and then press **SET**.
2. Use **←** and **→** to select **TAPE**, and then press **SET**.
 - You can also press **TAPE** here.
3. Use **←** and **→** to select **NEW**, and then press **SET**.
 - This displays a label mode selection screen.



Shows the function of the currently selected icon.

Selection boundary

4. Use the cursor keys to move the selection boundary to icon for the label mode you want to use.

To create this type of tape label:	Select this icon:
Original (Free Design) tape label (page 22)	
Sequentially numbered tape label (page 17)	
Barcode tape label (page 36)	
Large tape label (page 19)	
Tape label with logo (page 20)	


5. After you select a mode, press **SET**.
6. What you should do next depends on the label mode you selected in step 4. See the pages referenced in the table under step 4 for more information.

Creating and Printing a Sequentially Numbered Tape Label **1****2****3**

This label printer gives you a choice of six different numbering formats that you can use to print sequentially numbered labels from 0 to 99999.

Numbering Formats

• Format 1



Number

• Format 2




Up to 99 characters of text Number

• Format 3




Number Up to 99 characters of text

• Format 4




Up to 99 characters of text (COMMENT 1) Number Up to 99 characters of text (COMMENT 2)

• Format 5



Number Up to 99 characters of text

• Format 6



Number Up to 99 characters of text

Important!

- When printing sequentially numbered tape labels, printing is performed up to the number you specify. Before printing, make sure that the tape cartridge has enough tape left to finish the print operation. If the tape cartridge runs out of tape during a print operation, press **ESC** to cancel the print operation.

■ To create and print sequentially numbered tape labels


Example

File No.15 Receipt


File No.16 Receipt

File No.17 Receipt

- Press the **ON** to turn on the printer.
- Use **←** and **→** to select **TAPE**, and then press **SET**.
 - You can also press **TAPE** to enter the TAPE Mode.
- Use **←** and **→** to select **NEW**, and then press **SET**.
- Use the cursor keys to select the **1****2****3** icon, and then press **SET**.
 - This enters the Numbering Mode.
- Use **←** and **→** to select the numbering format, and then press **SET**. Here we will select Format 4.



6. Input the text for the COMMENT 1 box, and then press **SET**.
Here we will input "File".



Shows the starting number.

7. Change the starting number, if you want, and then press **SET**.

Here we want to number the labels from 15 through 17, so we would input 15 here.

- If you make a mistake and input the wrong number, delete the current number and re-input. You can specify a number up to five digits long.

8. Input the text for the COMMENT 2 box, and then press **SET**.

- Here we will input "Receipt".
- While inputting text in the Numbering Mode, you can also change the **DIRECTION** setting (page 25), **MIRROR** setting (page 26), and the **MARGINS** setting (page 26).

9. Use the cursor keys to select the number style you want, and then press **SET**.

- Here we will select **No.1**.


10. Use \uparrow and \downarrow to select **PRINT**, and then press **SET**.

11. Use \leftarrow and \rightarrow to specify the number of labels to be printed, checking the start and end numbers to make sure that they are correct, and then press **SET**.

- Here we want to print one set of labels numbered 15, 16, and 17, so we will specify 3 for the number of labels to be printed.
- For the number of labels to be printed, you can specify a value in the range of 1 to 100.

12. Use \leftarrow and \rightarrow to select the tape cut mode (page 38), and then press **SET**.

- Pressing **SET** starts the print operation and causes a screen like the one shown below to appear.
- If printing reaches the number 99999, the next number printed is 00000.
- If the message "LENGTH OF PRINT IS TOO LONG!" "TOO SHORT TO CUT!" appears, see pages 63, 67 for information about what you need to do.



The number that appears here depends on the label you created.

Important!

- Make sure that cut tape does not pile up in the area around the tape outlet. Tape building up around the tape outlet can cause the outlet to become blocked, causing a tape jam and malfunction of the printer.
- For information about saving tape label data, see page 54.

Controlling the Appearance of Your Labels


In steps from 6 through 8 of the basic procedure described above, you can also configure the following settings to control the appearance of your label.

- Direction (horizontal or vertical)
- Mirror printing (off or on)
- Margin size

See page 25 for information about how to configure these settings.

Creating and Printing a Large Tape Label **ABC**

Though your printer can print on tapes up to 24mm wide, there may be times that you need to produce even larger labels. You can do this by printing the large label in sections, and then assembling the sections into the final label.



Large label printed using two pieces of tape

Arranging the printed labels produces the large label.

Important!

- You must have a tape cartridge that is 12mm wide or wider loaded in the printer to perform this operation.

Example

Big (printed on two pieces of 12mm tape)

1. Press **ON** to turn on the printer.
2. Use **←** and **→** to select **TAPE**, and then press **SET**.
 - You can also press **TAPE** to enter the TAPE Mode.
3. Use **←** and **→** to select **NEW**, and then press **SET**.
4. Use the cursor keys to select **ABC**, and then press **SET**.
 - This enters the Enlarged Label Mode.
5. Input the label text and then press **SET**.
 - While inputting text in the Enlarged Label Mode, you can also change the **DIRECTION** setting (page 25) and the **MIRROR** setting (page 26).

6. Use **⊕** and **⊖** to select the size of the final label (how many pieces of tape will be used), and then press **SET**.

- Since we will be using two pieces of tape here, we will select **2 PIECES**.

Tape Width	Character Size		
	2 PIECES	3 PIECES	4 PIECES
12mm	24mm (1 5/16")	36mm (1 7/16")	48mm (1 7/8")
18mm	30mm (1 3/16")	45mm (1 3/4")	60mm (2 3/8")
24mm	30mm (1 3/16")	45mm (1 3/4")	60mm (2 3/8")

7. Use **⊕** and **⊖** to select **PRINT**, and then press **SET**.


8. Use **←** and **→** to specify what part of the large label you wish to print, and then press **⊖**.

- Here we want to select the entire label, so we will select **ALL**. If you want to print only one part of the large label, you can select 1, 2, 3, or 4, depending on the number of pieces that make up the large label.

9. Use **←** and **→** to select the tape cut mode (page 38), and then press **SET**.

- This starts printing.

10. The screen shown here appears after printing of the last piece is complete.



Combine the tapes to create the large label.

- If you use the above procedure to print on 18mm or 24mm tape, the tapes that are output will have blank margins along the bottom and/or the top of the upper tape and the top and/or the bottom of the lower tape. You will need to trim off these margins before combining the tapes. Another way to deal with margins is to use transparent tape. Then you can combine them without trimming, by laying one of the tapes over the other.

Controlling the Appearance of Your Labels

In step 5 of the basic procedure described above, you can also configure the following settings to control the appearance of your label.

- Direction (horizontal or vertical)
- Mirror printing (off or on)

See page 25 for information about how to configure these settings.

Creating and Printing a Tape Label with a Logo

LOGO

Your printer comes with 10 built-in logos that you can incorporate into your tape labels quickly and easily.

Built-in Logos



Important!

- You can incorporate built-in logos into tape labels that are printed using 18mm or 24mm tape only.

■ To create and print a label with a logo

1. Press **ON** to turn on the printer.
2. Use **◀** and **▶** to select **TAPE**, and then press **SET**.
 - You can also press **TAPE** to enter the TAPE Mode.
3. Use **◀** and **▶** to select **NEW**, and then press **SET**.
4. Use the cursor keys to select **LOGO**, and then press **SET**.
 - This enters the Logo Mode.




5. Use the cursor keys to select the logo you want to use, and then press **SET**.
6. Use **▲** and **▼** to select **PRINT**, and then press **SET**.
7. Use the number keys (or **◀** and **▶**) to specify the number of copies, and then press **▼**.
 - You can specify a value from 1 to 100 for the number of copies.
8. Use **◀** and **▶** to select the tape cut mode (page 38), and then press **SET**.
 - This starts the print operation. The screen shown below appears when printing is complete.



Creating and Printing an Original (Free Design) Tape Label

This section describes what you can do with the Free Design mode of the printer, which lets you design your own tape labels. All of the following sections whose titles start with “FREE DESIGN:” indicate features and functions that are available in the Free Design mode only.

■ To create a basic Free Design

1. Press **ON** to turn on the printer.
2. Use **←** and **→** to select **TAPE**, and then press **SET**.
 - You can also press **TAPE** here.
 - A LAST DATA icon will also appear on the Main Menu if there is input data left over from the last time you used the printer.
3. Use **←** and **→** to select **NEW**, and then press **SET**.
4. Use the cursor keys to select , and then press **SET**.
 - This enters the Free Design Mode.
5. Use the procedures described in the following “FREE DESIGN” sections to layout your label and input text.

FREE DESIGN: Using Text Blocks

In the example label shown below, “Promotion Plan” and “Retail Package Sample Data” are independent units called “text blocks,” or simply “blocks.” You can divided your tape label text into blocks and then apply the following settings on a block-by-block basis.

- Number of text lines (page 23)
- Text alignment (page 25)
- Character pitch (page 25)
- Block length (page 25)



Block 1


Block 2


- Two lines (page 23)

■ To layout a tape label using blocks

Example

To layout “Promotion Plan” and “Retail Package Sample Data” as separate blocks within the same tape label

1. In the Free Design Mode, input the text for the first block.
 - Here we will input “Promotion Plan”.
2. Press **FUNCTION** and then .
 - This inputs a “block mark,” which makes the text to the left of a block.





Block mark

Block marks appear on the display only. They are not printed on the tape.


3. Input the text for the next first block.

- Here we will input "Retail Package".
Indicates the block number where the cursor is currently located.



- To delete a block mark, move the cursor to the  symbol, and then press **DEL**. Note that you cannot delete a block mark by pressing the **BS** key.
- You can have up to 16 blocks inside of a single tape label layout.
- See page 24 of the Startup Guide for information about printing the label.
- For information about saving tape label data, see page 54.

Dividing Existing Text into Blocks

You can also divide text you have already input into blocks. Simply move the cursor to the location where you want to input a block mark, and then press **FUNCTION** .

FREE DESIGN: Using Multiple Lines in a Tape Label

This section explains how to use multiple lines in a label or a specific block in the Free Design Mode. Note that the maximum number of lines depends on the width of the tape you are using.

Important!

Tape Width	Maximum Number of Lines
6mm	2
9mm	3
12mm	5
18mm	8
24mm	8

- Note that the character size of the printed label will be adjusted by the printer automatically in accordance with the tape width and the number of lines (Auto Fit). This is true even if you specified the character size manually (page 31).


Example

New Branch

In Operation soon!

1. In the Free Design Mode, input the first line of text.
 - Here we will input "New Branch".


2. Press .




The newline mark indicates a newline operation.
Newline marks appear on the display only.
They are not printed on the tape.

3. Input the second line of text.
 - Here we will input "In Operation soon!".

The character size is adjusted automatically in accordance with the number of lines.



Label format
The lines indicate the number of lines in the label. Line thickness indicates character size.

- You can also insert a newline mark into existing text. Move the cursor to the desired location, and then press .
- To delete a newline mark, move the cursor to it and then press **DEL**. Note that you cannot delete a newline mark by pressing **BS**.
- An indicator like "5/8" appears for the label format indicator when the Small Font is selected for printing. This indicates that the total number of lines is 8, and the cursor is currently located in line 5. For details about using the Small Font, see page 34.
- The message "TOO MANY LINES!" appears if the width of the tape loaded in the printer is not compatible with the number of lines in the label you are creating. If this happens, reduce the number of lines or use a different width tape.
- See page 24 of the Startup Guide for information about printing the label.
- For information about saving tape label data, see page 54.

Other Tape Label Examples

Insert block mark (page 22).

Specify different character sizes for each line (page 31).

FREE DESIGN: Configuring Block Form Settings

You can use the procedure in this section to configure direction, alignment, pitch, and block length settings for each individual block.

Important!

- The following procedure applies when you have multiple blocks in a tape label. If there is only one block (no block markers), use the procedure under “FREE DESIGN: Configuring Label Form Settings” on page 26.

■ To configure block form settings

1. In the Free Design Mode, input the text you want, and divide it into blocks as required.
2. Move the cursor to the block whose form you want to change.
 - The cursor can be located anywhere within the block.
3. Press **FORM**.
4. Use \uparrow and \downarrow to select **BLOCK FORM**, and then press **SET**.
5. Use \uparrow and \downarrow to select **ONE BLOCK**, and then press **SET**.
 - Selecting **ALL BLOCKS** applies your settings to all of the blocks that make up the tape label.
6. Use \uparrow and \downarrow to select the setting you want to change, and \leftarrow and \rightarrow to change the currently selected setting.

When this setting is selected:	Use \leftarrow and \rightarrow to select the option you want:
DIRECTION	<ul style="list-style-type: none">• HORZ: Positions text from left to right• VERT: Positions text from top to bottom
ALIGN	<ul style="list-style-type: none">• LEFT: Aligns text flush left.• EQUAL: Equally spaces text to fill the entire space available.• CENTER: Centers text.• RIGHT: Aligns text flush right.• See page 29 for more information.
PITCH	<ul style="list-style-type: none">• Specify a value from 0.0 mm (0") to 31.9mm (1 1/4"). Changing this setting also causes the tape length to change accordingly.• This setting cannot be changed when EQUAL is selected for the ALIGN setting, and when FIX is selected for the B-LENGTH setting.
B-LENGTH	<ul style="list-style-type: none">• AUTO: Automatically adjusts block length in accordance with the number of characters.• FIX: Maintains a fixed block length in the range of 0cm (0") to 99.9cm (39 5/16"). See page 27 for more information.








- You can also change the **DIRECTION** setting when creating a label in the Numbering Mode (page 17) and the Enlarged Label Mode (page 19).



7. After all the block form settings are the way you want, press **SET**.



FREE DESIGN: Configuring Label Form Settings

Unlike the block form settings described in the previous section, label form settings are applied to the entire tape label, even if the label consists of multiple blocks.

■ To configure label form settings

1. In the Free Design Mode, input the text you want.
2. Press **FORM**.
 - If your label has only one block, the block form settings (page 25) will appear when you press **FORM**. If you perform the steps under “To configure block form settings” on page 25, the label form settings in step 4 of this procedure will appear when you press **SET** (or ) to complete the block form setting procedure (step 7 of “To configure block form settings”).
3. Use  and  to select **ALL FORM**, and then press **SET**.
4. Use  and  to select the setting you want to change, and  and  to change the currently selected setting.

When this setting is selected:	Use  and  to select the option you want:
MIRROR	<ul style="list-style-type: none"> • NORMAL: Prints the tape normally. • MIRROR: Prints the tape in mirror image onto special optionally available iron transfer tape.
PROPORTIONAL	<ul style="list-style-type: none"> • ON: Automatically adjusts letter spacing to the optional pitch. • OFF: Spaces letters using a uniform pitch.
SMOOTHING	<ul style="list-style-type: none"> • ON: Smoothes printed lines to eliminate jagged edges from text and graphics. • OFF: No smoothing performed.

When this setting is selected:	Use  and  to select the option you want:
BL-SPACE	<ul style="list-style-type: none"> • NARROW: 2mm (1/16") block spacing • WIDE: 4mm (3/16") block spacing • NONE: 0mm (0") block spacing
MARGINS	<ul style="list-style-type: none"> • NARROW: 6mm (1/4") margins • NONE: 0mm (0") margins • WIDE: 43mm (1 11/16") margins • MEDIUM: 20mm (13/16") margins • See page 27 for more information.
T-LENGTH	<ul style="list-style-type: none"> • AUTO: Automatically adjusts tape length in accordance with the number of characters. • FIX: Maintains a fixed tape length in the range of 0cm (0") to 99.9cm (39 5/16"). See page 27 for more information.
B-ALIGN	<ul style="list-style-type: none"> • LEFT: Aligns blocks flush left. • EQUAL: Equally spaces blocks to fill the entire space available. • CENTER: Centers blocks . • RIGHT: Aligns blocks flush right. • Note that this setting is available only when FIX is selected for the T-LENGTH setting. See page 29 for more information.

- You can also change the **MARGINS** setting when creating a label in the Numbering Mode (page 17), and the **MIRROR** setting when creating a label in the Numbering Mode (page 17) or the Enlarged Label Mode (page 19).

5. After all the label form settings are the way you want, press **SET**.

Margins

You can select from among the following four margin settings.

Note

- All of the margin measurements mentioned below are approximate.

NARROW



MEDIUM



WIDE



Important!

- Margins are not cut in the case of short tape lengths 31mm (1 1/4") for NARROW, 38mm (1 1/2") for MEDIUM, 50mm (1 15/16") for WIDE). After printing, you can use scissors to trim to the margin you want.

NONE



- Setting with the **NONE** setting makes it possible to print consecutive labels one after another.
- The auto tape cut operation is not performed when **NONE** is selected for the margins. To cut the tape, press **FUNCTION** and then **CUT**.









FREE DESIGN: Controlling the Length of a Tape Label

Tape label length is normally adjusted in accordance with the size and number of the characters in the label. This section explains how you can control the length of your labels.


There are two different ways to control label length:

- Specifying the length of each block contained in the label (fixed block length);
- Specifying the overall length of the label (fixed tape length).

■ To control label length using fixed block lengths

1. In the Free Design Mode, input the text you want, and divide it into blocks as required.
 - See page 22 for information about blocks.
2. Move the cursor to the block whose length you want to fix.
 - The cursor can be located anywhere within the block.
3. Press **FORM**.
 - If your label has only one block, advance directly to step 6 of this procedure.
4. Use  and  to select **BLOCK FORM**, and then press **SET**.
5. Use  and  to select **ONE BLOCK**, and then press **SET**.
 - If you want to apply your setting to all of the blocks in your label, select **ALL BLOCKS** instead.
6. Use  and  to select **B-LENGTH**.
7. Use  and  to change the setting to **FIX**.


8. Press .



Length value becomes highlighted.

9. Use the number keys, or the  (decrease) and  (increase) keys to change the block length setting.

- The appearance of the block length value on the display will change in accordance with your setting as described below.




[11.6cm]



Label can be printed as-is.

Sales Department




[9.6cm]



Text is condensed horizontally, and label is printed as-is.

Sales Department



[5.4cm]






Block length is printed longer than specified length value.

Sales Department

10. Press SET.

Fixed Block Length and the Label Format Indicator

Selecting **FIX** for the **B-LENGTH** setting causes the label format indicator in the upper right corner of the display to indicate the information described below.

<p>Label can be printed at specified length.</p> 	<p>Label will be printed at specified length with condensed characters.</p> 	<p>Label will be longer than specified length.*</p> 
---	---	---

* Text is printed at 50% normal size in the printing direction. The printed block length is longer than the specified length.

■ To control the overall label length using a fixed tape length

1. In the Free Design Mode, input the text you want.
2. Press **FORM**.
 - If your label has only one block, advance directly to step 4 of this procedure.
3. Use \curvearrowright and \curvearrowleft to select **ALL FORM**, and then press **SET**.
4. Use \curvearrowright and \curvearrowleft to scroll to the **T-LENGTH** setting screen.
5. Use \leftarrow and \rightarrow to change the setting to **FIX**, and then press \curvearrowleft .
6. Use the number keys, or the \leftarrow (decrease) and \rightarrow (increase) keys to change the label length setting.



Length value becomes highlighted.

- The appearance of the tape length value on the display will change in accordance with your setting as described below.

[20.6cm]



Label can be printed as specified.

20.5cm]




Label will be printed but the tape length will be longer than specified.

FREE DESIGN: Aligning Tape Label Text

This section explains how to align tape label text within a block and how to align blocks within a tape label.

Example 1: Aligning the term “Round Estimate①” in a block (fixed block length)




■ To align tape label text

1. In the Free Design Mode, input the text you want, and divide it into blocks as required.
 - See page 22 for information about blocks.
2. Move the cursor to the block whose text you want to align, and then press **FORM**.
 - Here we will move the cursor to the block that contains “Round”.
 - If your label has only one block, advance directly to step 5 of this procedure.
3. Use \curvearrowright and \curvearrowleft to select **BLOCK FORM**, and then press **SET**.
4. Use \curvearrowright and \curvearrowleft to select **ONE BLOCK**, and then press **SET**.
5. Use \curvearrowright and \curvearrowleft to scroll to the **ALIGN** setting screen.
6. Use \leftarrow and \rightarrow to select the alignment setting you want.
 - Each press of \leftarrow and \rightarrow cycles the setting between **EQUAL**, **CENTER**, **RIGHT**, and **LEFT**.


7. After selecting the alignment setting, use \odot and \ominus to scroll to the **B-LENGTH** setting screen.

8. Use \odot and \ominus to change the setting to **FIX**, and then press \ominus .



9. Use the number keys, or the \odot (decrease) and \ominus (increase) keys to increase the length of the block, and then press **SET**.

Example 2: Aligning blocks within a tape label




Important!


- The block alignment setting is applied only when **FIX** is selected for the **T-LENGTH** setting.

■ To align blocks within a tape label

- In the Free Design Mode, input the text you want, and divide it into blocks as required.
 - See page 22 for information about blocks.
- Press **FORM**.
 - If your label has only one block, advance directly to step 4 of this procedure.
- Use \odot and \ominus to select **ALL FORM**, and then press **SET**.
- Use \odot and \ominus to scroll to the **T-LENGTH** setting screen.
- Use \odot and \ominus to change the setting to **FIX**, and then press \ominus .



- If a block contains multiple lines, you can also align its text using the **B-LENGTH AUTO** setting. In this case, alignment will be performed on the shorter line of text as shown below.



6. Use the number keys, or the ◀ (decrease) and ▶ (increase) keys to change the label length setting.
 - Use a label length setting that is longer than the value that originally appears on the display.
7. Use ▼ to scroll to the **B-ALIGN** setting screen.
8. Use ◀ and ▶ to select the alignment setting you want.
 - Each press of ◀ and ▶ cycles the setting between **EQUAL**, **CENTER**, **RIGHT**, and **LEFT**.

FREE DESIGN: Changing the Size of Tape Label Text

Normally when you print, the printer automatically selects the optimum character size in accordance with the tape width and the number of text lines (Auto Fit).

You can also use the procedures in this section to override the Auto Fit feature and specify the character sizes you want to use.

There are two ways to specify the character size:

- Specifying the size of a string of characters
- Specifying the size of text lines

Important!

- Note that the character size values that you specify do not indicate absolute sizes, but rather multipliers. A size of “2×3” for example, specifies double the normal height and three times the normal width.

Specifying the Size of a String of Characters

You can specify the size in the range of 1×1 to 5×8 for a string of characters. Note that the maximum vertical size you can specify depends on the width of the tape you are using. For more information, see the “Tape Width and the Number of Lines and Character Sizes” on page 72.

1×1

Yes

4×4

Yes

2×3

Yes

5×6

Yes

- Note that how a character size specification affects text depends on whether the text is vertical or horizontal.

1×2 (Horizontal)

Yes

1×2 (Vertical)


> 0 S

■ To specify the size of a string of characters

Example: To change the size of “No Smoking” in the text “No Smoking here!” to 1x3

1. In the Free Design Mode, input the text you want.
2. Press **SIZE**.
3. Use \odot and \ominus to select **CHARACTER**, and then press **SET**.
4. With the highlighting located at the **HEIGHT** value, use \odot and \ominus to change the value.
 - Here we will change the value to 1.
 - You can also input a value with the number keys.
 - The printer will beep and not accept your input if you try to input a value that is not allowed.
5. Press \triangleright to move the highlighting to the **WIDTH** value.
 - If you specified the **HEIGHT** value by pressing a number key, the highlighting will move the **WIDTH** value automatically.
6. Use \odot and \ominus to change the **WIDTH** value, and then press **SET**.
 - Here we will change the value to 3.
7. Use \leftarrow and \rightarrow to move the cursor to the first character of the string to which you want to apply the size setting, and then press **SET**.
 - Here, align the cursor with “N”.
8. Use \leftarrow and \rightarrow to move the cursor to the last character of the string to which you want to apply the size setting, and then press **SET**.
 - Here we will select “No Smoking”.

Character Size




Auto Fit Mark

Character Size Mark


















- Character Size: This indicates the character size at the current cursor position.
- Character Size Mark: This mark indicates the point from which a character size specification is applied.
- Auto Fit Mark: This mark is inserted automatically by the printer to indicate that the text to the right of it will be adjusted automatically.









- The character size mark and auto fit mark appear on the display only. They are not printed in the label.
- To delete a character size mark, move the cursor to the mark and then press **DEL**.
- Deleting a character size mark causes the text to the right of it to assume the size of the next character size to the left. Deleting the last character size mark causes the size of the text to be set by the printer automatically in accordance with the width of the tape being used and the number of text lines.
- Note that a character size specification applies up to the end of the current block. A size specification does not span multiple blocks.



Specifying the Size of Text Lines

You can specify the size of text lines by selecting a format as shown below.

Number of Lines	Format	24 or 18mm Wide	12mm Wide	9mm Wide
1	A 	1 × 1	1 × 1	1 × 1
	B 	2 × 2	2 × 2	2 × 2*
	C 	3 × 3	3 × 3*	–
	D 	4 × 4	–	–
	E 	5 × 5*	–	–
2	A  	1 × 1 1 × 1	–	–
	B  	1 × 1 2 × 2	–	–
	C  	2 × 2 1 × 1	–	–
	D  	2 × 2 2 × 2	–	–
	E  	1 × 1 3 × 3*	–	–
	F  	3 × 3* 1 × 1	–	–

Number of Lines	Format	24 or 18mm Wide	12mm Wide	9mm Wide
3	A  	1 × 1 1 × 1 1 × 1	–	–
	B  	1 × 1 1 × 1 2 × 2*	–	–
	C  	1 × 1 2 × 2* 1 × 1	–	–
	D  	2 × 2* 1 × 1 1 × 1	–	–

* Smaller when the label includes a frame.

Important!

- The size of text lines cannot be specified in the case of 6mm wide tape.
- The size of text lines cannot be specified if there are four or more lines of text.
- The size of text lines cannot be specified if the label already contains size specifications for a string of characters.

Example:

Chicago Office


Business Performance

Line 1: 1×1 (Two lines, Format E)

Line 2: 3×3 (18mm wide tape)

1. In the Free Design Mode, input the text you want.
2. Press **SIZE**.
3. Use \triangleleft and \triangleright to select **LINE**, and then press **SET**.
4. Use the cursor keys to select the format you want, and then press **SET**.


Selected format



Small Font

- The printer has a Small Font setting, which it may select automatically depending on the number of lines (the number of text lines you input or the number of lines in the format you are using) and the tape width. An indicator appears next to the [SMALL FONT] indicator when the Small Font is in use.
- An indicator like "2/5" appears for the label format indicator when the Small Font is selected. This indicates that the total number of lines is 5, and the cursor is currently located in line 2.

Label format indicator



- Note the following about the Small Font.
 - Font settings are not applied (everything is printed using the same font).
 - The proportional setting is turned off.
 - Changing the style or effect while Small Font is being used can produce undesirable printing results.
 - Illustrations and user characters may not print correctly while Small Font is being used.

Either of the following will cause a text line size specification to be cancelled automatically.

- Changing the number of lines
- Specifying the size of a string of characters (page 32)

FREE DESIGN: Using Frames










The printer comes with a selection of built-in frames that you can use in your tape labels. See page 69 for a list of frames that are available.

Example



18mm wide tape, Frame Number 55

■ To add a frame to a tape label

1. In the Free Design Mode, input the text you want.
2. Press **FRAME**.
3. Use the cursor keys to select the frame you want, and then press **SET**.
 - Here we will select  .
4. Use  and  to select **PRINT**, and then press **SET**.
5. Use the number keys (or  and ) to specify the number of copies, and then press .
 - You can specify a value from 1 to 100 for the number of copies.
6. Use  and  to select the tape cut mode (page 38), and then press **SET**.
 - This starts the print operation.
 - The **BOX** text attribute is not applied when printing with a frame.

Frames and the Number of Lines

The number of lines that can be printed with a frame depends on the width of the tape.

	24/18mm	12mm	9mm	6mm
Number of Lines with Frame	Up to 6	Up to 3	Up to 2	1

Creating a Barcode Tape Label

Your printer lets you create and print tape labels with barcodes.

Supported Barcode Types

■ EAN

EAN-13
EAN-8
UPC-A
UPC-E

■ ITF

ITF

■ CODE39

■ CODABAR (NW-7)

Important!


- Use a 12mm or wider tape cartridge when printing barcodes.
- You can input up to 60 characters of comment text above a barcode.
- Be sure to check each barcode for proper reading. Make the following adjustments if you experience difficulties reading the barcodes produced by this printer.
 - Lighten the print density (page 55).
 - Increase the barcode size (step 8 of “To create a barcode tape label” on this page).
 - Select **FULL CUT** or **UNCUT** for the tape cut mode (page 38).
- The following tapes work best for barcode printing. Letters in parentheses indicate tape model names.
 - White tape, black printing (WE)
 - White tape, blue printing (WEB)
 - Yellow tape, black printing (YW)

Example



18mm wide tape cartridge

■ To create a barcode tape label

1. Press **ON** to turn on the printer.
2. Use **⏪** and **⏩** to select **TAPE**, and then press **SET**.
 - You can also press **TAPE** to enter the TAPE Mode.
3. Use **⏪** and **⏩** to select **NEW**, and then press **SET**.
4. Use the cursor keys to select , and then press **SET**.
5. Use the cursor keys to select a barcode type, and then press **SET**.
 - If you selected ITF, CODE39, or CODABAR as the barcode type, use the next screen that appears to specify whether to use a check digit, and then press **SET**.
6. Input comment text if you want, and then press **SET**.
 - If you do not want to input any comment text, simply press **SET** without inputting anything.
7. Input the data for the barcode, and then press **SET**.
8. Use **⏴** and **⏵** to select the barcode size, and then press **SET**.
9. Use **⏴** and **⏵** to select **PRINT**, and then press **SET**.
10. Use the number keys (or **⏪** and **⏩**) to specify the number of copies, and then press **⏵**.
 - You can specify a value from 1 to 100 for the number of copies.
11. Use **⏪** and **⏩** to select the tape cut mode (page 38), and then press **SET**.
 - This starts the print operation.
 - For information about saving tape label data, see page 54.

Barcode Specifications

Barcode	Check Digit*1	Printed Digits*3	Number of Input Digits*4	Automatically Added Digits		Input Characters*8
					Check Digit*1	
EAN-13	Yes	13 digits	12 digits	–	1 digit	Numerals
EAN-8	Yes	8 digits	7 digits	–	1 digit	Numerals
UPC-A	Yes	12 digits	11 digits	–	1 digit	Numerals
UPC-E	Yes*2	6 digits	6 digits	–	–	Numerals
ITF	No	4 to 22 digits	4 to 22 digits Even numbers only*5	–	–	Numerals
	Yes	4 to 22 digits	3 to 21 digits Odd numbers only*6	–	1 digit	
CODE39	No	4 to 22 digits	2 to 20 digits	2 digits*7	–	Numerals Alpha A to Z
	Yes	4 to 22 digits	1 to 19 digits	2 digits*7	1 digit	Symbols (-)(.)(Space) (\$)(/)(+)(%)
CODABAR (NW-7)	No	4 to 22 digits	4 to 22 digits	–	–	Numerals Symbols (-)(\$)(:)(/) (.)(+)
	Yes	4 to 22 digits	3 to 21 digits	–	1 digit	Alpha (first, last only)*9 A to D

*1 The check digit is automatically calculated in accordance with input data. For EAN-13, EAN-8, and UPC-A, and when using a check digit with ITF, the check digit is appended at the end of the printed digits. When using a check digit with CODE39 or CODABAR, the check digit is appended one digit before the final digit.

*2 UPC-E includes a check digit, but it is not printed as a numeral below the bar code.

*3 The number of digits printed below a bar code equals the input characters plus automatically appended characters.

*4 An error message is displayed whenever there are insufficient digits. The printer will not allow input of too many digits.

*5 An error message appears and printing is impossible if an odd number of digits are input when an ITF check digit is not being used. Append a zero to the beginning of the digits and re-input.

*6 An error message appears and printing is impossible if an even number of digits are input when an ITF check digit is being used. Append a zero to the beginning of the digits and re-input.

*7 Both the start code and end stop code of CODE39 must be asterisks.

*8 An error message appears and printing is impossible if any characters other than those specified here are used.

*9 With CODABAR, A, B, C, or D can be used as the start code and stop code. An error message appears and printing is impossible if any other character is used.

Using Tape Labels

Tape Cut Modes

When you are printing a series of tape labels, the tape cut mode controls whether or not a cut operation is performed for each label. You can also specify the type of cut operation that should be performed.

Note that cutting certain types of tape can damage the cutter blade. Be sure to use the correct tape cut mode settings whenever printing on the type of tapes listed below.

When printing on this type of tape:	Always use this tape cut mode setting:
<ul style="list-style-type: none">• Iron transfer tape	FULL CUT
<ul style="list-style-type: none">• Magnetic tape• Reflective tape	UNCUT

Types of Tape Cuts

There are two types of tape cuts, half cut and full cut.


■ Half cut

With half cut, only the label part is cut, without cutting the paper backing.

- Half cut is may not be possible with 6mm wide tape

■ Full cut

Full cut cuts both the tape and its backing.




Cut Modes

You can select from among four different cut modes.

- Note that the type of cut operation performed depends on the cut mode and the margin setting. See "Cut Modes and Margins" on page 40 for more information.
- No cutting (neither full nor half) is performed when **NONE** is selected for the **MARGINS** setting.
- Half cutting and full cutting may not be performed when label tapes are the following lengths: less than about 31mm (1 1/4") when using the **NARROW** margin setting, less than about 38mm (1 1/2") when using the **MEDIUM** margin setting, or less than about 50mm (1 15/16") when using the **WIDE** margin setting. In this case, use scissors to cut the labels after printing is complete.


■ CONT HALF CUT

- CONT HALF CUT performs a half cut between labels, and a full cut when the end of the printing is reached.




■ FULL+HALF CUT

- FULL+HALF CUT perform a full cut at the end of each label, and a half cut near the beginning of each label to make the backing paper easier to remove.




■ FULL CUT

- FULL CUT performs a full cut at the end of each label.
- Use this setting when printing on iron transfer tape.
- When using the **NARROW** and **MEDIUM** margin settings, this setting automatically performs a full cut to trim off excess tape.



■ UNCUT

- When UNCUT is selected, the printer does not perform any cut operation between labels.
- This setting is best when you want to print labels without spaces between them, which saves label tape.
- Be sure to select UNCUT when printing on magnetic tape and reflective tape. After printing is complete, press **FUNCTION** and then **FEED** to feed the tape, and then cut it with a pair of scissors.



Using Magnetic Tape and Reflective Tape

Special handling is required when printing on magnetic tape and reflective tape. Whenever printing on magnetic tape or reflective tape, select UNCUT as the tape cut mode, and cut the tape using a pair of scissors as described below.

Important!

- Using the printer's built-in cutter to half cut or full cut magnetic tape or reflective tape will shorten the service life of the cutter blade, and can damage the cutter mechanism.
 1. Select **NONE** for the **ALL FORM MARGINS** setting (page 26), or **UNCUT** for the tape cut mode.
 2. Print the tape.
 3. Press **FUNCTION FEED** to feed the tape.
 4. Use a pair of scissors to cut the tape.

Cut Modes and Margins

The following shows how the tape cut type (full or half) and margin length are affected by the tape cut mode and margin settings.

Cut Mode		CONT HALF CUT			FULL+HALF CUT			FULL CUT			UNCUT		
Margin	Cut Timing	Trimming of excess at beginning of label	Cutting between each label	Cutting after printing is complete	Trimming of excess at beginning of label	Cutting between each label	Cutting after printing is complete	Trimming of excess at beginning of label	Cutting between each label	Cutting after printing is complete	Trimming of excess at beginning of label	Cutting between each label	Cutting after printing is complete
	NARROW	Cut	Half cut	Half cut	Full cut	Half cut	Full cut	Full cut	Full cut	Full cut	Full cut	None	None
Margin		18.5mm (3/4")	3mm (1/8")	3mm (1/8")	18.5mm (3/4")*1 5mm (3/16")*2	3mm (1/8")	3mm (1/8")	23.5mm (15/16")	3mm (1/8")	3mm (1/8")	23.5mm (15/16")	3mm (1/8")	3mm (1/8")
MEDIUM	Cut	Half cut	Half cut	Full cut	Half cut	Full cut	Full cut	Full cut	Full cut	Full cut	None	None	None
	Margin	11.5mm (7/16")	10mm (3/8")	10mm (3/8")	11.5mm (7/16")*1 5mm (3/16")*2	10mm (3/8")	10mm (3/8")	23.5mm (15/16")	10mm (3/8")	10mm (3/8")	23.5mm (15/16")	10mm (3/8")	10mm (3/8")
WIDE	Cut	Half cut	Half cut	Full cut	Half cut	Full cut	Full cut	None	Full cut	Full cut	None	None	None
	Margin	5mm (3/16")	21.5mm (7/8")	21.5mm (7/8")	5mm (3/16")*1 5mm (3/16")*2	21.5mm (7/8")	21.5mm (7/8")	-	21.5mm (7/8")	21.5mm (7/8")	-	21.5mm (7/8")	21.5mm (7/8")
NONE	Cut	None	None	None	None	None	None	None	None	None	None	None	None
	Margin	-	-	-	-	-	-	-	-	-	-	-	-

*1: Printing of first label

*2: Printing of second and subsequent labels

Part 3 - Inputting and Editing Label Text

This section describes everything you need to know about deleting and editing text you have already input.

Moving the Cursor

Use the cursor keys to move the cursor around the display and position it for deleting and editing characters.

■ To move the cursor

To perform this operation:	Press this:
Move the cursor left	⬅
Move the cursor right	➡
Move the cursor up	⬆
Move the cursor down	⬇
Move the cursor to the beginning of the current line of text	FUNCTION ⬅
Move the cursor to the end of the current line of text	FUNCTION ➡

Basic Alpha Numeric Input

The following operation shows you the basic procedures for inputting letters and numbers. Note that it assumes that a text input screen is already on the display.

To input alpha-numeric characters

Example: ABXYZ 1234567890

1. Input the characters by typing them on the printer's keyboard.
 - To input the uppercase letters, you can use either **SHIFT** or **CAPS**. With **SHIFT** you must shift the keyboard for each character. With **CAPS** the keyboard keeps its uppercase/ lowercase setting until you press **CAPS** again.
 - Press **SPACE** to input spaces.
 - If you input a wrong character, press **BS** or **DEL** to delete it and input again.
2. When you reach the end of a line of text, press **SET**.

About the CODE key

The **CODE** key makes it possible to input punctuation needed for a number of different languages. The following shows the key operations you should use for each of the characters formed using the **CODE** key.

■ CAPS on

Key Operation	Input	Key Operation	Input	Key Operation	Input
CODE U	Ü	CODE Z	Ž	CODE 5	^
CODE O	Œ	CODE C	Ç	CODE 6	∨
CODE P	À	CODE N	Ñ	CODE 7	◊
CODE A	Æ	CODE 1	˘	CODE 8	/
CODE J	Ö	CODE 2	˘	CODE 9	˘
CODE K	Ä	CODE 3	¨	CODE 0	˘
CODE L	Ø	CODE 4	˘		

■ CAPS off



Key Operation	Input	Key Operation	Input	Key Operation	Input
CODE U	ü	CODE L	ø	CODE 4	˘
CODE O	œ	CODE Z	ž	CODE 5	^
CODE P	à	CODE C	ç	CODE 6	∨
CODE A	æ	CODE N	ñ	CODE 7	◊
CODE S	ß	CODE 1	˘	CODE 8	/
CODE J	ö	CODE 2	˘	CODE 9	˘
CODE K	ä	CODE 3	¨	CODE 0	˘

Example: To input á **CODE 1 () A**

Inputting Symbols and Special Characters

The **SYMBOL** menu provides you with a choice of symbols, dingbats, and special number formats, in addition to Greek and Russian letters.

To use the SYMBOL menu

1. With the cursor at the location where you want to input a symbol, dingbat, number, Greek letter, or Russian letter, press **SYMBOL** to display the **SYMBOL** menu.
2. Use  and  to select the type of character you want, and then press **SET**.
 - Pressing **SET** causes a menu of symbols, dingbats, number formats, Greek letters, or Russian letters to appear.
 - To exit the **SYMBOL** menu without selecting anything, press **ESC**.
3. Use the cursor keys to select the character you want to input, and then press **SET**.
 - Pressing **SET** returns to the input screen, with the symbol, dingbat, number, Greek letter, or Russian letter you selected input at the location where the cursor was located when you displayed the **SYMBOL** menu.
 - See page 68 for a complete list of symbols, dingbats, number formats, Greek letters, and Russian letters that are available from each menu.

Inputting Illustrations

Your printer gives you a choice of 124 illustrations that you can use in your labels.

To input illustrations

1. With the cursor at the location where you want to input an illustration, press **ILLUST** to display the ILLUST menu.
2. Use the cursor keys to select the illustration you want to input, and then press **SET**.
 - Pressing **SET** returns to the input screen with the illustration you selected input at the location where the cursor was located when you displayed the ILLUST menu.
 - See page 68 for a complete list of illustrations that are available.

Deleting an Individual Character

You can delete an individual character with either the **BS** key or the **DEL** key. The only difference between the operations of these two keys is the location of the cursor.

To delete a character using the BS key

Example: To change the word “commmputer” to “computer”.

1. Use ⏪ and ⏩ to move the cursor under “p”.
2. Press **BS** twice to delete the two m’s to the left of the cursor, shifting “puter” to the left as you do.

To delete a character using the DEL key



Example: To change the word “commmputer” to “computer”.

1. Use ⏪ and ⏩ to move the cursor under the first (far left) “m”.
2. Press **DEL** twice to delete the two m’s at the cursor’s position, shifting “mputer” to the left as you do.







Clearing Input Text

Use the following steps to clear text on the input screen.

To clear all text

1. Press **FUNCTION** and then **BS** (CLS).
 - If you are deleting all text in the Free Design label mode, a screen will appear to offer you a choice between **ALL** or **PART**. Use  and  to select **ALL**, and then press **SET**.
2. In response to the confirmation message that appears, press **SET**.
 - This clears all the text from the input screen.
 - If you want to abort the clear operation without deleting anything, press **ESC** in place of **SET**.

To delete a range of text (Free Design)

1. Press **FUNCTION** and then **BS** (CLS).
2. Use  and  to select **PART**, and then press **SET**.
3. Use  and  to move the cursor to the first character of the range of text from which you want to delete, and then press **SET**.
4. Use  and  to move the cursor to the last character of the range of text to which you want to delete, and then press **SET**.

Text Editing

You can set up the label printer so it either inserts new input between existing characters, or overwrites existing characters with new input. Note the following example.

Example

Existing text: ABCDEFGHI
Cursor location: E
New input: XXX





Insert

Result: ABCDXXXEFGHI

Overwrite

Result: ABCDXXXHI

To switch between overwrite and insert

1. Press **FUNCTION** and then **SET UP** to display the SET UP menu.
2. Use  and  to select **INPUT** and then press **SET**.
3. On the next screen that appears, use  and  to select **INSERT**, or **OVERWRITE** and then press **SET**.
 - The CAPS indicator on the display is highlighted when overwrite is turned on. The CAPS indicator appears normally (unhighlighted) when insert is turned on.



Using Phrase Memory

Phrase memory provides storage of nine phrases you can recall and input into your labels. Initially, phrase memory records 1 through 8 are preset with often-used label phrases. You can use these as they are or replace them with your own text.









The following are the initial contents of the phrase memory records.

- 1 Digital Image
- 2 Date Recorded:
- 3 Backup Data
- 4 Confidential
- 5 Hit Album
- 6 Omnibus
- 7 My Favorites
- 8 Recorded At:
- 9 <Empty>







To recall a phrase

1. While inputting text, press **PHRASE MEMORY**.
 - This displays a list of available phrases.
2. Use  and  to select the phrase you want to recall, and then press **SET**.
 - This recalls the phrase you selected and inputs it into the input screen.
 - You can also select a phrase by inputting its record number, from 1 through 9.
 - If the phrase you selected causes the number of input characters to exceed the allowable limit, the error message "ENTIRE PHRASE COULD NOT BE RECALLED!" appears. The phrase is partially input, up to the allowable limit.

To create new phrase memory text

1. Press **PHRASE MEMORY**.
2. Use  and  to select **[DATA EDIT]**, and then press **SET**.
3. Use  and  to select **MAKE**, and then press **SET**.
4. Use  and  to select **NEW**, and then press **SET**.
 - The **NEW / STRING→PHRASE** screen does not appear if there is not text currently input on the text input screen.
5. On input screen that appears, input the text that you want, and then press **SET**.
6. Use  and  to select the phrase memory where you want to store the text, and then press **SET**.
7. In response to the confirmation message that appears, press **SET** to save the phrase or **ESC** to abort.

To save input text in phrase memory

1. While inputting the text you want to save on the input screen, press **PHRASE MEMORY**.
2. Use  and  to select **[DATA EDIT]**, and then press **SET**.
3. Use  and  to select **MAKE**, and then press **SET**.
4. Use  and  to select **STRING→PHRASE**, and then press **SET**.
5. On the input screen that appears, check the text and make any changes that you want and then press **SET**.

When you save input text in phrase memory

- If the text includes character size marks, new line marks, block marks and so on, these characters are saved as spaces.
- If the text includes 49 characters or more, the first 49 characters are saved as input text.

6. Use \uparrow and \downarrow to select the phrase memory where you want to store the text, and then press **SET**.
7. In response to the confirmation message that appears, press **SET** to save the phrase or **ESC** to abort.

To edit a phrase memory record

1. Press **PHRASE MEMORY**.
2. Use \uparrow and \downarrow to select **[DATA EDIT]**, and then press **SET**.
3. Use \uparrow and \downarrow to select **EDIT**, and then press **SET**.
4. Use \uparrow and \downarrow to select the phrase memory record whose contents you want to edit, and then press **SET**.
5. On the text screen that appears, check the text and make any changes that you want, and then press **SET**.
6. Use \uparrow and \downarrow to select the phrase memory where you want to store the text, and then press **SET**.
7. In response to the confirmation message that appears, press **SET** to save the phrase or **ESC** to abort.

To delete a phrase memory record

1. Press **PHRASE MEMORY**.
2. Use \uparrow and \downarrow to select **[DATA EDIT]**, and then press **SET**.
3. Use \uparrow and \downarrow to select **DELETE**, and then press **SET**.
4. Use \uparrow and \downarrow to select the phrase memory record whose contents you want to delete, and then press **SET**.
5. In response to the confirmation message that appears, press **SET** to delete the phrase or **ESC** to abort.

Using Copy and Paste

You can copy text data you have input in one location, and paste it into another location.

■ To copy text

1. Input the text you want to copy.
2. Press **FUNCTION** and then **COPY**.
 - The message "COPY OPERATION COMPLETE" appears and the input screen appears when the copy operation is complete.
 - The above operation will leave the displayed text the way it is, and save a copy of it in memory.
 - You can copy up to 49 characters at one time. If there are more than 49 characters on the display, only the first 49 characters are selected.
 - You can have up to nine copies in memory. The 10th copy operation causes the oldest copied text to be deleted to make room for the newly copied text.
 - Any character size, newline, and block marks included in the text are automatically replaced with spaces when the text is copied.

■ To paste copied text

1. When inputting text, press **PASTE**.
2. On the list of copied text that appears, use \uparrow and \downarrow to select the text you want, and then press **SET**.
 - This pastes the selected data at the current cursor location.
 - If the text you are copying causes the maximum number of input character limit to be exceeded, the message "TOO MANY CHARACTERS! SOME WERE NOT PASTED" appears and some of the text is not pasted.


User Characters

You can create up to four user characters and store them in memory. You can create a character from scratch, or you can use an existing character or symbol as a basis for your new character.

■ To create a user character from scratch

1. Press **FUNCTION** and then **USER CHR**.
 - If the screen is blank or if the cursor is located where there is no character, performing the above step will take you directly to the User Character Drawing Screen. In this case, skip step 3, and go directly to step 4.
2. Use \uparrow and \downarrow to select **MAKE** and then press **SET**.
3. Use \uparrow and \downarrow to select **NEW** and then press **SET**.
 - The NEW/USE INPUT CHAR screen does not appear if there is no input character at the cursor location on the text input screen.

User Character Drawing Screen



4. Use the following operations to draw the character you want.

To do this:	Do this:
Move the cursor	Use the cursor keys.
Make the cursor jump to the left, right, top or bottom of the drawing screen	Press FUNCTION followed by \leftarrow , \rightarrow , \uparrow , or \downarrow .
Draw a black dot	Press 1 so BLACK is highlighted on the display.
Draw a white dot	Press 2 so WHITE is highlighted on the display.
Draw a line of black dots	Press 1 and 3 so BLACK and CONTINUE are highlighted on the display, and then use the cursor keys to move the cursor.
Draw a line of white dots	Press 2 and 3 so WHITE and CONTINUE are highlighted on the display, and then use the cursor keys to move the cursor.

- Note that you can draw and delete straight lines only. You cannot draw and delete diagonal lines. To create a diagonal line, you need to input each of its dots, one-by-one.
- Each press of **3** while **BLACK** or **WHITE** is highlighted toggles the **CONTINUE** setting on (highlighted) and off (unhighlighted).

5. After you are finished drawing the character you want, press **SET**.

6. Use the cursor keys to select the user character area where you want to store the character, and then press **SET**.

7. In response to the confirmation message that appears, press **SET** to store the character.



■ To create a user character using an existing character

1. Input the character or symbol you want to use as a basis for your new character and locate the cursor under the character.
2. Press **FUNCTION** and then **USER CHR**.
3. Use \uparrow and \downarrow to select **MAKE** and then press **SET**.
4. Use \uparrow and \downarrow to select **USE INPUT CHAR** and then press **SET**.
5. Perform steps 4 through 7 under "To create a user character from scratch" to create and save the new character.



■ To create a user character using user character you created previously

1. Press **FUNCTION** and then **USER CHR**.
2. Use \uparrow and \downarrow to select **EDIT** and then press **SET**.
3. Use the cursor keys to select the character you want to use as the basis for your new character and then press **SET**.
4. Perform steps 4 through 7 under "To create a user character from scratch" to create and save the new character.

To recall a user character

1. With the cursor located in the input screen where you want to input the user character, press **FUNCTION** and then press **USER CHR.**
2. Use  and  to select **RECALL** and then press **SET.**
3. Use the cursor keys to select the user character you want to recall and then press **SET.**

To delete a user character

1. Press **FUNCTION** and then **USER CHR.**
2. Use  and  to select **DELETE** and then press **SET.**
3. Use the cursor keys to select the user character you want to delete and then press **SET.**
4. In response to the confirmation message that appears, press **SET** to delete the selected character or **ESC** to abort.

Part 4 - Controlling the Appearance of Text

The operations in this section explain how to select fonts, and how to use font attributes (styles and effects) to make text more attractive and eye-catching.

Selecting a Font

Your printer gives you a choice of the following five fonts.

- New Sans-serif (SANS-SERIF)

ABC

- New Sans-serif Italic (SANS-SERIF ITC)

ABC

- New Sans-serif Rounded (SANS-SERIF RND)

ABC

- New Roman (ROMAN)

ABC

- New Roman Italic (ROMAN ITC)

ABC

You can specify a font for the text you have just input or you can specify a default font that is used automatically whenever you create a new label. The current font setting is indicated by the pointer along the right side of the display.

SMALL FONT

When printing on a disc, SMALL FONT is used for printing when the character size is 2mm, regardless of the current font setting. In the case of tape printing, SMALL FONT is used for printing when the number of lines (number of input lines or number of lines in the selected format) and the tape width require it. A pointer appears next to the **SMALL FONT** indicator when the SMALL FONT is in use.

- The following points all apply while SMALL FONT is in use.
- All font settings are ignored. Everything is printed using the same font.
- The proportional setting is turned off.
- Changing the style or effect while SMALL FONT is in use can produce undesirable printing results.
- Illustrations and user characters may not print correctly while SMALL FONT is in use.

To change the default font setting

1. Press **FUNCTION** and then **SET UP** to display the SET UP menu.
 2. Use \uparrow and \downarrow to select **DEFAULT FONT** and then press **SET**.
 3. Use \uparrow and \downarrow to select the font you want to use as the default, and then press **SET**.
- The default font you specified will be used first for all new labels. When inputting text, you can use the procedure above to change the font to another style, if you want.

To change the font of text you have just input

1. After inputting the text you want, press **FONT**.
2. Use \uparrow and \downarrow to select the font you want to change to and then press **SET**.
3. On the next screen that appears, select the range of text to which you want to apply your font setting, and then press **SET**.

To apply the font setting to this text:	Select this option:
All of the text in the label	ALL
All of the text in the current block (Free Design Mode only)	BLOCK
All of the text in the current line	LINE
Specific characters (Free Design Mode only)	CHARACTER


- If you select **ALL** for Free Design Mode text, press **SET**. This will apply the setting and return to the text input screen.
- Selecting any other setting in the Free Design Mode cause a range setting screen like the one shown below to appear. Use steps 4 and 5 to specify the range of text.



4. Use \leftarrow and \rightarrow to move the cursor to the first character of the string of text to which you want to apply the FONT setting, and then press **SET**.
5. Use \leftarrow and \rightarrow to move the cursor to the last character of the string of text to which you want to apply the FONT setting, and then press **SET**.
 - This will apply the setting and return to the text input screen.

Using STYLE Menu Attributes

The STYLE menu lets you apply the following attributes to your text.



- Note that STYLE menu text attributes cannot be applied to illustrations or user characters.

■ To apply STYLE menu text attributes

1. Input the text whose attributes you want to change.
2. Press **STYLE**.
3. Use \odot and \ominus to select **STYLE**, and then press **SET**.
 - If there is no EFFECT option on the screen that appears, jump directly to step 4.
4. Use \odot and \ominus to select the STYLE setting you want, and then press **SET**.
 - Selecting **NORMAL** cancels the current STYLE menu setting.


5. Use \odot and \ominus to select the range of text for the STYLE setting you want, and then press **SET**.

To apply the STYLE setting to this text:	Select this option:
All of the text in the label	ALL
All of the text in the current block (Free Design Mode only)	BLOCK
All of the text in the current line	LINE
Specific characters (Free Design Mode only)	CHARACTER

- If you select **ALL** for Free Design Mode text, press **SET**. This will apply the setting and return to the text input screen.
- Selecting any other setting in the Free Design Mode cause a range setting screen like the one shown below to appear. Use steps 6 and 7 to specify the range of text.



6. Use \leftarrow and \rightarrow to move the cursor to the first character of the string of text to which you want to apply the STYLE setting, and then press **SET**.
7. Use \leftarrow and \rightarrow to move the cursor to the last character of the string of text to which you want to apply the STYLE setting, and then press **SET**.
 - This will apply the setting and return to the text input screen.



A pointer appears to indicate the current STYLE setting: [A] (BOLD), [A] (OUTLINE), [A] (SHADOW), [A] (RAISED). No pointer is shown when NORMAL is selected.

Using EFFECT Menu Attributes

The EFFECT menu lets you apply the text attributes shown below to label text in the Free Design Mode.

Examples

SHADING	UNDERLINE	BOX(CCHARACTER)	BOX(TEXT)
E-Mail	<u>E-Mail</u>	E-Mail	E-Mail

■ To apply EFFECT menu text attributes

1. Input the text whose attributes you want to change.
2. Press **STYLE**.
3. Use \uparrow and \downarrow to select **EFFECT**, and then press **SET**.
4. Use \uparrow and \downarrow to select the EFFECT setting you want, and then press **SET**.
 - To remove all of the currently selected text attributes, select **CANCEL** and then press **SET**.
5. Use \uparrow and \downarrow to specify how you want the effect applied, and then press **SET**.
6. Use \leftarrow and \rightarrow to move the cursor to the first character of the string to which you want to apply the EFFECT setting, and then press **SET**.
7. Use \leftarrow and \rightarrow to move the cursor to the last character of the string to which you want to apply the EFFECT setting, and then press **SET**.
 - This will apply the setting and return to the text input screen.

■ To remove all EFFECT settings

1. Press **STYLE**.
2. Use \uparrow and \downarrow to select **EFFECT**, and then press **SET**.
3. Use \uparrow and \downarrow to select **CANCEL**, and then press **SET**.
 - If you want to remove a particular EFFECT setting, use the cursor keys to select its name, and then press **SET**.^{*1}
4. Use \uparrow and \downarrow to select **CHARACTER**^{*2}, and then press **SET**.
^{*2} You can select other settings if you want.
5. Use \leftarrow and \rightarrow to move the cursor to the first character of the string of text from which you want to remove EFFECT settings, and then press **SET**.
6. Use \leftarrow and \rightarrow to move the cursor to the last character of the string of text from which you want to remove EFFECT settings, and then press **SET**.
^{*1} If you want to remove a particular EFFECT setting, press **DEL** instead of **SET**.

Combining Effects

SHADING, UNDERLINE, and BOX effects can be combined, if you want. Simply apply one effect, and then repeat the above procedure to apply another one.

For Sale

SHADING + BOX
(TEXT)

For Sale

SHADING + UNDERLINE

For Sale

SHADING + UNDERLINE + BOX
(CHARACTER)

- Using **BOX** and **UNDERLINE** in combination with certain character sizes can cause the underline and the lower line of the box to overlap with each other.

Part 5 - Saving, Recalling and Deleting Labels

To save a label

1. Create the label you want to save.
2. After you finish inputting text, the following screen will appear on the printer display.



3. Use \uparrow and \downarrow to select **STORE**.
4. Press **SET**.
5. Input up to five characters for the label name, and then press **SET**.



Total amount of memory used by currently stored labels.

6. In response to the confirmation message that appears, press **SET** to save the label or **ESC** to abort.

To recall a label

1. Press ON to turn on the printer.
2. Use \leftarrow and \rightarrow to select **DISC** or **TAPE**, and then press **SET**.
 - You can also press **DISC** or **TAPE** to enter the DISC or the TAPE Mode.
3. Use \leftarrow and \rightarrow to select **STORED DATA**, and then press **SET**.
4. Use \uparrow and \downarrow to select **RECALL**, and then press **SET**.
5. Use \uparrow and \downarrow to scroll through the label names until the one you want to recall is displayed.
6. Press **SET** to display the label.
 - Now you can print the label or make any changes you want in it.

To delete a label

1. Press ON to turn on the printer.
2. Use \leftarrow and \rightarrow to select **DISC** or **TAPE**, and then press **SET**.
 - You can also press **DISC** or **TAPE** to enter the DISC or the TAPE Mode.
3. Use \leftarrow and \rightarrow to select **STORED DATA**, and then press **SET**.
4. Use \uparrow and \downarrow to select **DELETE**, and then press **SET**.
5. Use \uparrow and \downarrow to scroll through the label names until the one you want to delete is displayed.
6. Press **SET**.
7. In response to the confirmation message that appears, press **SET** to delete the label or **ESC** to abort.
 - If there are multiple labels stored in memory, deleting a label will cause the next label name to appear. You can repeat the above procedure to delete other labels, if you want.
 - To exit the label delete operation, press **ESC**.

Part 6 - Configuring the Printer Setup

The printer has a SET UP screen that you can use to configure a variety of basic settings.

■ To configure the printer setup

1. Press **ON** to turn on the printer.
2. Press **FUNCTION** and then **SET UP**.
3. Use **▲** and **▼** to select the SET UP item whose setting you want to change, and then press **SET**.
4. Use the cursor keys to change it.

When this setting is selected:	Change its setting like this:
DEFAULT FONT	• Use ▲ and ▼ to select the font (page 51).
INPUT	• Use ▲ and ▼ to select INSERT or OVERWRITE (page 44).
CONTRAST	• Use ◀ and ▶ to adjust the display contrast.
DENSITY	• Use ▲ and ▼ to select DISC Mode or TAPE Mode. • Use ◀ and ▶ to adjust the print density setting.
SOUND	• Use ▲ and ▼ to turn printer sound effect on or off.
LANGUAGE	• Use ▲ and ▼ to select the display language you want to use.
cm/inch	• Use ▲ and ▼ to select centimeters (cm) or inches as the unit of measurement.
DEMO PRINT	• Use ▲ and ▼ to select DISC Mode or TAPE Mode, and then press SET to start demo printing.

Demo Printing


Demo printing uses built-in data to demonstrate the type of disc printing and tape label printing that can be performed by the printer.

Important!





- If there is label data from your last label layout session is still in memory, performing a demo print will delete it. If you think you will need the data later, save it in memory (page 54) before performing a demo print.

■ To perform disc demo printing









1. Make sure an ink ribbon cassette is loaded in the printer.
 - See page 11 of the Startup Guide for information about loading ink ribbon cassettes.
2. If the printer is on, press **OFF** to turn it off.
3. Press **ON** to turn on the printer.
4. Press **FUNCTION** and then **SET UP**.
5. Use **▲** and **▼** to select **DEMO PRINT**, and then press **SET**.
6. Use **▲** and **▼** to select **DISC**, and then press **SET**.
7. Use **▲** and **▼** to select the demo data you want to print, and then press **SET**.
8. Use **▲** and **▼** to select **PRINT**, and then press **SET**.



9. Use **◀** and **▶** to select **DISC**, and then press **SET**.
 - If you want to print a disc case label, select **TAPE** instead
 - If you want to print a disc case label, see page 13 of the Startup Guide for information about loading tape cartridges.

10. Use  and  to select the print area you want to print, and then press **SET**.
11. Insert a disc into the printer.
12. Press **SET** to start printing.
 - Both DATA 1 and DATA 2 print in both the upper print area and the lower print area of the disc.
13. After printing is complete, use  and  to select **EXIT**, and then press **SET**.
14. In response to the confirmation message that appears, press **SET**.

■ To perform tape demo printing

1. Make sure a tape cartridge is loaded in the printer.
 - See page 13 for the Startup Guide for information about loading tape cartridges.
2. If the printer is on, press  to turn it off.
3. Press  to turn on the printer.
4. Press **FUNCTION** and then **SET UP**.
5. Use  and  to select **DEMO PRINT**, and then press **SET**.
6. Use  and  to select **TAPE**, and then press **SET**.
7. Use  and  to select **PRINT**, and then press **SET**.
8. Confirm that 1 is specified for the number of copies and **CONT HALF CUT** is specified for the tape cut mode.
 - You can change the number of copies and the tape cut mode (page 38) settings if you want.
 - If you are using a non-standard type of tape, select the appropriate tape cut mode (page 38) for the tape you are using.
9. Press **SET** to start printing.
 - The demo print contents depend on the width of the tape cartridge currently loaded in the printer.

10. After printing is complete, use  and  to select **EXIT**, and then press **SET**.
11. In response to the confirmation message that appears, press **SET**.

Power Requirements

You can run the printer by using its bundled AC adaptor to plug it into a power outlet. It can also run on commercially available alkaline batteries.



■ Using Batteries

Note

- The printer can run on eight AA-size alkaline batteries. Be sure to use alkaline batteries only.


1. Turn over the printer and remove the battery cover.

- Never bend or twist the battery cover, or otherwise subject it to rough handling. Doing so creates the risk of printer malfunction.




2. Load a set of eight new batteries.

- Make sure the positive (+) and negative (-) poles of the batteries are facing in the proper directions.



3. Replace the battery cover.



Important!

- The printer may suddenly turn off during printing if battery power goes low. Because of this, use of the bundled AC adaptor is recommended to power the printer.
- Because of the affect cold has on batteries, the "LOW BATTERY!" may appear prematurely when the temperature is below 10°C(50°F). If this happens, move the printer to a location where the temperature is within the operating temperature range (10°C to 35°C (50°F to 95°F))

Battery Life

Disc Label Printing

- Printing of approximately 150 discs*
Normal temperature (20°C (68°F)), one printing per disc.

Label Tape Printing

- Printing of approximately two 18mm tape cartridges under standard printing conditions*

* When printing text or graphics that contain large areas of black, and printing under cold temperatures can shorten battery life for both disc label printing and label tape printing.

Caring for the Printer


Disc and tape label printing can become unclear if the printer's print head and rubber roller become dirty. Perform the following steps to clean the print head and rubber roller.

■ To use a cotton swab for cleaning

Important!

- Use only a cotton swab or some other soft material to clean the print head and rubber roller. Use of a very fine type cotton swab is recommended.

1. Press the cassette cover release and open the cover.
 - If a tape cartridge or the ink ribbon cassette adaptor is loaded in the printer, remove it.
2. Use a cotton swab moistened with alcohol to thoroughly swab the areas where the print head and rubber roller come into contact.



- You can rotate the rubber roller by pressing **FUNCTION** and then **FEED**.
- You can also use a commercially available cassette tape recorder head cleaning kit to clean the print head.

■ To clean with a cleaning tape

Note

- Use an optionally available cleaning tape (XR-24CLE) to perform this procedure.

1. Press the cassette cover release and open the cover.
 - If there is a tape cartridge or ink ribbon cassette adaptor loaded in the printer, remove it.
2. Load the cleaning tape into the printer.
3. Press **ON** to turn on the printer.
4. Press **FUNCTION** and then **FEED** to feed the tape one or two times.
 - For details about using the cleaning tape, see the instructions that come with it.

Cleaning the Printer Exterior

Wipe the exterior of the printer with a cloth moistened with plain water.

Wring all excess liquid from the cloth before wiping the printer.

Never use benzene, alcohol, thinner, or other volatile agents to clean the printer exterior. Doing so can damage the case.

Troubleshooting

Consult the troubleshooting tables below whenever you start to have problems with the printer or application. If you can't find the solution to your problem below, contact your original retailer or your nearest authorized CASIO service center.

Symptom	Possible Cause	Recommended Action
Nothing appears on the display when I press ON .	The display contrast setting needs adjustment.	Adjust the display contrast setting. (page 55)
	The AC adaptor is not connected properly.	Make sure the AC adaptor is properly connected. (Startup Guide, page 7)
	Battery power is low or the wrong type of batteries are loaded in the printer.	Change to AC adaptor power or replace the current batteries with a fresh set of AA-size alkaline batteries (supplied by you). (page 57)
	Batteries are not loaded properly.	Reload the batteries properly. (page 57)
The printing operation is finished normally, but nothing is printed.	Only spaces are input for the label.	Input the text you want to print.
	The file imported from a computer does not contain any data.	Re-import the data.

Symptom	Possible Cause	Recommended Action
Printing is not clear. Printing is poor quality. Printing is too light.	The print head or roller is dirty.	Clean the print head and roller. (page 58)
	Battery power is low.	Change to AC adaptor power or load a fresh set of batteries (supplied by you). (page 57)
	Improper print density	Adjust the print density. (page 55)
Cannot print.	Battery power is low or the wrong type of batteries are loaded in the printer.	Change to AC adaptor power or load a fresh set of AA-size alkaline batteries (supplied by you). (page 57)
I can't input text.	The FUNCTION key has been pressed.	Press ESC to cancel the FUNCTION key operation.
I can't get a connection between the printer and a computer.	The COMPUTER LINK button has not been pressed.	Press the COMPUTER LINK button to establish a connection.
	The bundled USB cable is not connected properly.	Re-connect the cable properly.
	The printer is turned off.	Press ON to turn on the printer.
	The USB driver is not installed correctly.	Unplug the USB cable and the plug it back in again.
	Though the USB driver is installed correctly, data communication is not possible for some reason.	Try using a different USB port on your computer, or try using a different USB cable.

DISC Mode

Symptom	Possible Cause	Recommended Action
The printing operation is finished normally, but nothing is printed.	The ink ribbon is used up.	Load a new ink ribbon cassette (option). (Startup Guide, page 11)
Printing is not clear. Printing is poor quality. Printing is too light.	Any of the following can interfere with proper printing. <ul style="list-style-type: none"> • A disc printing surface that is not smooth and flat • A disc printing surface that has a design or lines printed on it • A disc printing surface that supports ink jet printing only 	Use a disc that meets the requirements described in the bundled "Printing Precautions" or at the following Internet URL. http://world.casio.com/ds/media/ You can also try adjusting the print density to make it darker. (page 55)
	The ink ribbon cassette is not loaded properly.	Re-load the ink ribbon cassette properly.
The printed color is different from the ink ribbon color.	The color of the final printout is affected by both the color of the ink ribbon and the color of the disc you are printing on.	Try using a lighter color disc or a darker color ink ribbon.

Symptom	Possible Cause	Recommended Action
The printing is not positioned correctly on the disc.	Improper alignment of the disc when it is placed in the printer.	Use the positioning guide when aligning the disc. (Startup Guide, page 21)
The disc stops part way through printing.	The power cord plug or the AC adaptor is not plugged in as far as it will go.	Correctly connect the power cord and the AC adaptor. (Startup Guide, page 7)
	The printer is malfunctioning.	If you cannot easily remove the disc from between the print head and roller, do not try to force it. Insert a thin object into the print head release button hole (Startup Guide, page 4) and press to release the print head. This should allow you to remove the disc. After removing the disc, press the release lever inside the cassette case (Startup Guide, page 4) to its original position before trying to print again. If you are still unable to remove the disc from the printer, contact your retailer or your nearest CASIO service center.
	Battery power is low or the wrong type of batteries are loaded in the printer.	Use the bundled AC adaptor to power the printer, or replace the current batteries with a fresh set of AA-size alkaline batteries.

Symptom	Possible Cause	Recommended Action
I cannot insert a disc into the printer.	A tape cartridge is loaded in the printer.	A disc cannot be inserted into the printer while a tape cartridge is loaded. Remove the tape cartridge and replace it with an ink ribbon cassette. (Startup Guide, page 11)
Printing will not start.	The disc is not positioned correctly in the printer.	Remove the disc and then re-insert it straight into the left side of the slit along the top of the printer. (Startup Guide, page 20)

TAPE Mode

Symptom	Possible Cause	Recommended Action
The printing operation is finished normally, but nothing is printed.	The tape is used up.	Replace the tape cartridge with a new one.
Printing is not clear. Printing is poor quality. Printing is too light.	The tape cartridge is not loaded properly.	Re-load the tape cartridge properly.
	The print density setting is too light.	Adjust the print density to make it darker.
No tape comes out when I press PRINT .	The cassette cover is not closed completely.	Close the cassette cover. (Startup Guide, page 5)
	The tape is used up.	Replace the tape cartridge with a new one. (Startup Guide, page 13)
	The tape is jammed.	Remove the tape cartridge and pull out the jammed tape. Use scissors to cut off the tape you pulled out. Load the tape cartridge back into the printer. (Startup Guide, page 13) Important! Note the following while printing is in progress. <ul style="list-style-type: none"> • Do not allow the tape outlet to become blocked. • Do not touch the tape coming out of the printer. • Do not open the cassette cover. • Do not turn off the printer.

Symptom	Possible Cause	Recommended Action
No tape comes out when I press PRINT .	Battery power is low.	Change to AC adaptor power or load a fresh set of batteries (supplied by you). (page 57)
The ink ribbon is coming out of the tape outlet together with the tape.	Slack in the ink ribbon when the tape cartridge was loaded in the printer.	Remove the tape cartridge. After making sure that the ink ribbon is not broken, take up all the slack. Reload the tape cartridge into the printer. (Startup Guide, page 13) Important! <ul style="list-style-type: none"> Always make sure you remove all slack from the ink ribbon before loading a tape cartridge into the printer. If the ink ribbon is broken, replace the tape cartridge with a new one.
The tape will not cut.	The tape cutter is dull.	Have the tape cutter replaced by your retailer or your local CASIO service center.
	Tape is jammed in the tape outlet.	Turn off the printer, remove the tape cartridge, and remove the jammed label.
	NONE is selected for the MARGINS setting of the format being used.	Change the MARGINS setting to NARROW, MEDIUM or WIDE . (page 26)
	UNCUT is selected for the tape cut mode.	Change the tape cut mode setting to something other than UNCUT . (page 38)

Symptom	Possible Cause	Recommended Action
The tape will not cut.	The label is too short. (Less than approximately 31mm (1 1/4") with narrow margins Less than approximately 38mm (1 1/2") with medium margins Less than approximately 50mm (1 15/16") with wide margins)	Use scissors to cut the labels after printing is complete.
The printer will not half cut.	The tape cutter is dull.	Have the tape cutter replaced by your retailer or your local CASIO service center.
	FULL CUT or UNCUT is selected for the tape cut mode.	Change the tape cut mode setting to CONT HALF CUT or FULL+HALF CUT .
	You are printing on magnetic tape.	Half cutting is not supported for magnetic tape. Use scissors to cut the labels after printing is complete. <ul style="list-style-type: none"> Select UNCUT for the tape cut mode whenever printing on magnetic tape or reflective tape (page 39).
The label does not stick.	The label is too short. (Less than approximately 31mm (1 1/4") with narrow margins Less than approximately 38mm (1 1/2") with medium margins Less than approximately 50mm (1 15/16") with wide margins)	Use scissors to cut the labels after printing is complete.
	The backing paper has not been removed.	Remove the backing paper. (Startup Guide, page 25)
	The location or the surface is not compatible.	Do not try to affix a label to a surface that is rough, wet, oily, or dirty. (Startup Guide, page 25)

Error Messages

Message	Cause and Action	See page:
DATA ERROR! INITIALIZE THE PRINTER!	<ul style="list-style-type: none"> You are trying to operate the printer without initializing its memory first. <p>→ Initialize printer memory.</p>	Startup Guide, page 8
ENTIRE PHRASE COULD NOT BE RECALLED!	<ul style="list-style-type: none"> The text in the phrase memory you are trying to recall will cause the number of characters to exceed the allowable limit for the location where you are inserting it. <p>→ Re-input so the recalled phrase memory text does not cause the allowable number of characters to be exceeded.</p>	46
ILLEGAL CHARACTERS!	<ul style="list-style-type: none"> You are attempting to input characters that are not allowed for bar code printing. <p>→ Delete the disallowed characters.</p> <ul style="list-style-type: none"> For a CODABAR barcode, you are trying to use a character other than A, B, C, or D as the start code or stop code. <p>→ Re-input the correct character.</p>	36
	<ul style="list-style-type: none"> In the case of a numbering label, you are trying input a space after a number. <p>→ Delete the space after the number.</p>	17

Message	Cause and Action	See page:
INPUT A VALUE!	<ul style="list-style-type: none"> You are trying to print numbering labels without any input. <p>→ Input the numbers you want.</p>	17
LABEL LONGER THAN SETTING SET/ESC	<ul style="list-style-type: none"> To print, press SET. To cancel printing, press ESC. You can then decrease the number of characters, change to a longer tape setting, or select auto tape length. 	26
LENGTH OF PRINT IS TOO LONG!	<ul style="list-style-type: none"> You are trying to print something that is longer than the length of tape available. <p>→ Make the label shorter or reduce the number of copies.</p>	26
LINK ERROR! CHECK ALL CONNECTIONS!	<ul style="list-style-type: none"> The USB cable is not connected securely to the USB port. <p>→ Plug the USB cable securely into the USB port.</p> <ul style="list-style-type: none"> The computer is shut down. <p>→ Start up the computer.</p>	Read this first
LOAD A TAPE CARTRIDGE	<ul style="list-style-type: none"> There is no tape cartridge loaded in the printer or the tape cartridge is not loaded correctly. <p>→ Check the tape cartridge.</p>	Startup Guide, page 13

Message	Cause and Action	See page:
LOW BATTERY!	<ul style="list-style-type: none"> • Battery power is low. → Replace the batteries or use the bundled AC adaptor to power the printer. • Temperature is below 10°C (50°F) → Move the printer to a location where the temperature is within the operating temperature range (10°C to 35°C (50°F to 95°F)). 	57
LOW BATTERY! CONTINUE TO PRINT? SET/ESC	<ul style="list-style-type: none"> • Battery power is low. → Replace the batteries or use the bundled AC adaptor to power the printer. • Temperature is below 10°C (50°F) → Move the printer to a location where the temperature is within the operating temperature range (10°C to 35°C (50°F to 95°F)). 	57
MEMORY FULL!	<ul style="list-style-type: none"> • There is not enough memory available to save the data you are trying to save. → Delete memory data you no longer need and try again. 	54

Message	Cause and Action	See page:
NO DATA!	<ul style="list-style-type: none"> • You are trying to perform a recall, edit, or delete operation on a phrase memory that does not contain any data. → Select a different phrase memory. • You are trying to recall or delete memory data when there is no data in memory. → Store data in memory before performing the current operation. 	45
NO INPUT TEXT!	<ul style="list-style-type: none"> • You are attempting a print or preview operation when there is no text input. → Input text before printing or previewing. 	Startup Guide, pages 20 and 24
NOT ENOUGH DIGITS!	<ul style="list-style-type: none"> • You are trying to print a bar code that does not have the required number of digits. → Re-input the correct number of digits. 	36
NOT ENOUGH INK RIBBON FOR NEXT PRINT	<ul style="list-style-type: none"> • There is not enough ink ribbon left to perform the current print job. → After printing finishes, replace the ink ribbon cassette before starting the next print. 	Startup Guide, page 11

Message	Cause and Action	See page:
NOT ENOUGH MEMORY! SET/ESC	<ul style="list-style-type: none"> • There is not enough memory available to save the data you are editing. → To edit and print without saving the data, press SET to continue. If you want to save the data, delete memory data you no longer need. 	54
NOW PRINTING	<ul style="list-style-type: none"> • The printer has overheated. → Stand by and printing will resume as soon as the printer returns to normal temperature. * If the "NOW PRINTING" message remains on the display and it appears as if printing will not resume, contact your retailer or your nearest CASIO service center. 	—
ODD (EVEN) NUMBER OF DIGITS!	<ul style="list-style-type: none"> • You specified no check digit for an ITF barcode and input an odd number of digits. → Append a zero to the beginning and re-input. • You specified a check digit for an ITF barcode and input an even number of digits → Append a zero to the beginning and re-input. 	36
PENDING DATA WILL BE LOST CONTINUE? SET/ESC	<ul style="list-style-type: none"> • To delete the text, press SET. • If you do not want to delete the text, press ESC. 	—

Message	Cause and Action	See page:
PRINT ERROR! CHECK THE TAPE CARTRIDGE!	<ul style="list-style-type: none"> • The tape became jammed during printing. → Turn off the printer and remove the tape cartridge. Next, remove the jammed tape. • There is something stuck in the auto tape cutter. → Turn off the printer and remove the tape cartridge. Next, remove whatever is stuck in the auto tape cutter. 	Startup Guide, page 13
	<ul style="list-style-type: none"> • There is dirt, tape pieces, or other foreign matter stuck to the rubber roller. → After removing the foreign matter from the rubber roller, clean the rubber roller. 	58
	<ul style="list-style-type: none"> • The printer is being used in an area that is exposed to direct sunlight or some other source of bright light, causing malfunction of its optical sensor. → Turn off the printer and then move it to a location that is not exposed to bright light. * If the steps described above do not clear the error message, contact your retailer or your nearest CASIO service center. 	—


Message	Cause and Action	See page:
PRINT ERROR! LOAD AN INK RIBBON CASSETTE!	<ul style="list-style-type: none"> There is no ink ribbon cassette loaded in the printer or the ink ribbon cassette is not loaded correctly. → Check the ink ribbon cassette. 	Startup Guide, page 11
PRINT ERROR! NO INK RIBBON!	<ul style="list-style-type: none"> The ink ribbon cassette has reached its end. → Replace the ink ribbon cassette 	Startup Guide, page 11
PRINT ERROR! PLACE DISC IN PRINTER CORRECTLY!	<ul style="list-style-type: none"> The disc is not inserted properly into the printer. → Insert the disc properly. 	Startup Guide, page 20
SAME NAME ALREADY USED!	<ul style="list-style-type: none"> The name you are trying to assign to data is already being used by previously stored data. → Input a different name 	54

Message	Cause and Action	See page:
THIS IS THE WRONG TYPE OF TAPE CARTRIDGE!	<ul style="list-style-type: none"> The cassette cover is not closed completely. → Close the cassette cover. The label you are trying to print or recall is not compatible with the currently loaded tape cartridge. → Turn off the printer and replace the tape cartridge. 	Startup Guide, page 13
	<ul style="list-style-type: none"> You replaced the tape cartridge in the TAPE mode. → Turn off the printer and replace the tape cartridge. 	Startup Guide, page 13
	<ul style="list-style-type: none"> An ink ribbon cassette is loaded in the printer. → Turn off the printer and load the appropriate tape cartridge. 	Startup Guide, pages 11 and 13
TOO MANY BL!	<ul style="list-style-type: none"> The layout already contains 15 block marks. → Delete block marks you no longer need. 	22
TOO MANY CHARACTERS! SOME WERE LOST	<ul style="list-style-type: none"> You are trying to save input text in phrase memory that contains more than 49 characters. → Only the first 49 characters will be saved. Edit the text as required to make sure it is less than 50 characters long. 	45

Message	Cause and Action	See page:
TOO MANY CHARACTERS! SOME WERE NOT COPIED	<ul style="list-style-type: none"> You are trying to copy text that contains more than 49 characters. → Decrease the number of characters you are copying. 	47
TOO MANY CHARACTERS! SOME WERE NOT PASTED	<ul style="list-style-type: none"> Pasting copied text will cause the number of characters to exceed the allowable limit for the location where you are pasting. → Re-input so the pasted text does not cause the allowable number of characters to be exceeded. 	47
TOO MANY LINES TO FRAME!	<ul style="list-style-type: none"> Printing with a frame will cause your label to have more than the allowable number of lines. → Decrease the number of lines or change to a wider tape. 	35
TOO MANY LINES!	<ul style="list-style-type: none"> You are trying to print a label that has more than the allowable number of lines. → Decrease the number of lines or change to a wider tape. 	23

Message	Cause and Action	See page:
TOO SHORT TO CUT! SET/ESC	<p>The unused tape at the beginning of a numbering label cannot be cut or cutting between labels is not possible.</p> <ul style="list-style-type: none"> To print without cutting, press SET. After printing is complete, use scissors to cut the labels. To print with auto cutting, change the settings to increase the margin width (from NARROW to MEDIUM, or from MEDIUM to WIDE). Left and right margins can auto cutting can be ensured by selecting FULL CUT for the tape cut mode and WIDE for the margins setting. 	26, 38

Illustrations



Symbols, Dingbats, and Special Characters

● SYMBOL

, . : ; . ? ! ' ' " " „ << >> ¿ ¡ () [] { } < > <<>>

/ \ \$ ¢ £ Fr ¥ # & * @ § % ‰

+ - × = ≠ ÷ ± < > ≤ ≥ ° ~ ¶

→ ← ↑ ↓ ↘ ↙ ↗ ↖ → ← ↑ ↓ ™ ® © ≡

∞ ⊥ ∴ oz lb. in. ft. °F °C ° f ℓ ° €

● DINGBAT

● NUMBER

① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨ ⑩ ⑪ ⑫ ⑬ ⑭ ⑮ ⑯ ⑰ ⑱

⑲ ⑳ I II III IV V VI VII VIII IX X i ii iii iv v vi

vii viii ix x ½ ¼ ¾ 00 01 02 03 04 05 06 07 08 09 10

11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28

29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46

47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64

65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82

83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99

90 91 92 93 94 95 96 97 98 99 00 01 02 03 04 05 06 07

08 09 10 11 12 13 14 15 16 17 18 19

● GREEK, RUSSIAN

Α Β Γ Δ Ε Ζ Η Θ Ι Κ Λ Μ Ν Ξ

Ο Π Ρ Σ Τ Υ Φ Χ Ψ Ω α β γ δ

ε ζ η θ ι κ λ μ ν ξ ο π ρ σ

τ υ φ χ ψ ω Α Β Γ Δ Ε Ε̇ Ж

З И Й К Л М Н О П Р С Т У Ф











Х Ц Ч Ш Щ Ъ Ы Ь Э Ю Я а б в













г д е ё ж з и й к л м н о п




р с т у ф х ц ч ш щ ъ ы ь э

ю я







Disc Label Formats

Type	Number	Format	Input Item	Vertical Size (mm/inch)	Maximum Number
FOR-MAT	1		TITLE	12/1/2"	12
	2		TITLE	9/3/8"	16
	3		TITLE1	6/1/4"	24
			TITLE2	6/1/4"	24
	4		TITLE	9/3/8"	16
			COMMENT	3/1/8"	49
	5		COMMENT	3/1/8"	49
			TITLE	9/3/8"	16
	6		TITLE	6/1/4"	24
			COMMENT	3/1/8"	49
7		COMMENT	3/1/8"	49	
		TITLE	6/1/4"	24	
8		TITLE1	3/1/8"	49	
		TITLE2	3/1/8"	49	
		TITLE3	3/1/8"	49	
9		TITLE	6/1/4"	24	
		COMMENT1	3/1/8"	49	
		COMMENT2	3/1/8"	49	
10		COMMENT1	3/1/8"	49	
		COMMENT2	3/1/8"	49	
		TITLE	6/1/4"	24	

Type	Number	Format	Input Item	Vertical Size (mm/inch)	Maximum Number
FOR-MAT	11		TITLE	6/1/4"	24
			ITEM1~4	3/1/8"	24 (x4)
	12		TITLE1~4	3/1/8"	49 (x4)
	13		ITEM1~8	3/1/8"	24 (x8)
	14		TITLE	6/1/4"	24
			COMMENT	3/1/8"	49
			ITEM1~4	2/1/16"	18 (x4)
	15		TITLE	6/1/4"	24
			ITEM1~4	2/1/16"	37 (x4)
	16		TITLE	6/1/4"	24
ITEM1~8			2/1/16"	18 (x8)	
17		ITEM1~8	2/1/16"	37 (x8)	
18		ITEM1~16	2/1/16"	18 (x16)	
LOGO	1		LOGO	—	—
	2		LOGO	—	—
			TITLE	6/1/4"	12
	3		LOGO	—	—
TITLE1~2			3/1/8"	24 (x2)	
4		LOGO	—	—	
		TITLE1~3	3/1/8"	24 (x3)	

Type	Number	Format	Input Item	Vertical Size (mm/inch)	Maximum Number
AUTO	1		TITLE	15~3 ⁹ / ₁₆ "~1 ¹ / ₈ "	49
	2		TITLE1	6~3 ¹ / ₄ "~1 ¹ / ₈ "	49
			TITLE2	6~3 ¹ / ₄ "~1 ¹ / ₈ "	49

Numbering Formats

Number	Format	Input Item	Tape Width (mm)				
			24	18	12	9	6
1		NUMBER					
2		COMMENT, NUMBER					
3		NUMBER, COMMENT					
4		COMMENT1, NUMBER, COMMENT2,	○	○	○	○	○
5		COMMENT, NUMBER					
6		NUMBER, COMMENT					

Tape Width and the Number of Lines and Character Sizes

The number of print lines and the vertical character size depends on the tape width and format being used.

		Tape Width (mm)				User's Guide page
		6	9	12	18, 24	
Maximum Number of Print Lines	Normal Font	1 line	1 line	2 lines	4 lines	23
	Small Font	2 lines	3 lines	5 lines	8 lines	34 50
Maximum vertical size	Normal Font	1	2	3	5	31
	Small Font	1	2	3	4	34 50
Total vertical size	Normal Font	1	Up to 2	Up to 2*	Up to 4*	23
	Small Font	Up to 2*	Up to 3*	Up to 5*	Up to 8*	31 34 50

* Total when there are multiple lines

Supported Tape Widths

■ DISC

	Tape Width (mm)				
	6	9	12	18	24
Case Label	×	×	×	○	○

■ TAPE

	Tape Width (mm)				
	6	9	12	18	24
Free Design	○	○	○	○	○
Frame	○	○	○	○	○
Enlarged Label	×	×	○	○	○
Bar Code	×	×	○	○	○
Numbering	○	○	○	○	○
Logo	×	×	×	○	○

Enlarged Label Printing Tape Widths and Character Sizes

	Tape Width (mm)			
	6, 9	12	18	24
2 Pieces	×	24 ¹⁵ / ₁₆ "	30 ¹³ / ₁₆ "	30 ¹³ / ₁₆ "
3 Pieces	×	36 ⁷ / ₁₆ "	45 ³ / ₄ "	45 ³ / ₄ "
4 Pieces	×	48 ⁷ / ₈ "	60 ² / ₈ "	60 ² / ₈ "

(mm/inch)

* Printing on 18mm or 24mm tape creates blank margins along the bottom and the top of each tape. Trim off these margins before combining the tapes, or print on transparent tape. Then you can combine the tapes without trimming, by laying one over the other.

Specifications

Model : CW-L300

Input

Keyboard Layout : Typewriter (QWERTY)

Character Types

Alpha : 52 (A to Z, a to z); 99 (Á, ß, Ç, etc.)

Numbers : 10

Greek : 48

Russian : 66

Symbols : 281

Illustrations : 124

User : Memory for storage of four characters

Display

Type : Liquid crystal display (96 × 64 dots, 12 columns × 4 lines)

Input Area : 12 columns × 1 line (non Free Design Mode)

12 columns × 3 lines (Free Design Mode)

Printing

Resolution : 200dpi

Print System : Thermal transfer

Disc Printing

Approximate Speed : 8.3mm (5/16")/second

Print Width : Approximately 16mm (5/8")

Print Length : Approximately 74mm (2 15/16")

Label Tape Printing

Approximate Speed : 6.0 mm (1/4")/second

Print Width : Approximately 16mm (5/8")

- 4mm (3/16") (6mm tape)
- 7mm (1/4") (9mm tape)
- 10mm (3/8") (normal printing 12mm tape)
- 12mm (1/2") (Enlarged printing 12mm tape)
- 16mm (5/8") (18mm or 24mm tape)
- Actual print speed depends on printing environment and conditions.

Characters : Bitmap

Fonts : New Sans-serif, New Sans-serif Italic, New Sans-serif Rounded, New Roman, New Roman Italic

Print Directions : Horizontal, Vertical, Mirror*

* Vertical and mirror printing are possible on tape only.

Character Styles : Normal, Bold, Outline, Shadow, Raised

Number of Disc Printing Lines : 8 maximum

Number of Tape Label Printing Lines : 1 to 2 lines on 6mm tape

1 to 3 lines on 9mm tape

1 to 5 lines on 12mm tape

1 to 8 lines on 18mm or 24mm tape

Memory

Text : Approximately 4,000 characters for DISC Mode;

2,000 characters for TAPE Mode

Copy and Paste : Up to 49 characters; 9 entries

Phrase Memory : 9 phrases, up to 49 characters per phrase

General

Power Requirements : AC adaptor (AD-2105S); Eight AA-size alkaline batteries

Memory Backup : Built-in battery

Memory Backup Battery Life : As noted on the sticker on the back of the

printer (at 20°C (68° F))

Replacement requires charged maintenance by CASIO service center.

Power Consumption : 15W

Auto Power Off : Approximately six minutes after last key operation

- Auto Power Off disabled under AC adaptor power and when printer is connected to a computer.

Dimensions : 88 (H) × 215 (W) × 246 (D) mm


(3 7/16" H × 8 7/16" W × 9 11/16" D)

Approximate Weight : 1.4 kg (3.1 lbs) excluding batteries

Operating Temperature : 10°C to 35°C (50° F to 95° F)



CASIO Europe GmbH Bornbarch
10, 22848 Norderstedt, Germany



**Batterij niet weggooien,
maar inleveren als
KCA**

CASIO®

CASIO COMPUTER CO., LTD.

6-2, Hon-machi 1-chome
Shibuya-ku, Tokyo 151-8543, Japan

MO0504-B Printed in China/Imprimé en Chine

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>