


LUMIÈRE®




ASPEN 1900-AA

39W (max) PAR20 Metal Halide

50W (max) MR16 Halogen
Low Voltage (12V)

FEATURES

- Includes anchor bolts & template
- Adjustable aperture w/ locking mechanism
- Patented LumaLevel™ mounting/leveling system
- Machined aluminum housing, cast base
- Stainless steel hardware
- UL / cUL listed
- Three (3) year warranty



SAMPLE NUMBER: 1900-AA-24-MH39PAR20-120-BK

MODEL	SIZE	SOURCE	VOLTS	FINISH	OPTIONS
1900-AA Adjustable aperture	24	<i>Metal Halide</i> MH39PAR20 39W / PAR20 / medium <i>Includes integral core & coil ballast. Lamp not included.</i>	120, 208 240, 277 347	<i>Painted</i> BK Black BZ Bronze CS City silver VE Verde WT White	EL Electronic HID ballast (120/277V) in lieu of core & coil IT Integral transformer for 12V MR16 source <i>See "Accessories & Technical Data" section of catalog for remote transformers</i>
	30	<i>Halogen</i> 50MR16 50W / MR16 / GU5.3 <i>12V remote or integral transformer required - not included Lamp not included</i>	120/12 277/12		
<i>To ship anchor bolt/template kit in advance</i> LAB Less anchor bolts & template (order kit separately - 7048PK)					




ASPEN 1900-OA

39W (max) PAR20 Metal Halide

50W (max) MR16 Halogen
Low Voltage (12V)


FEATURES

- Includes anchor bolts & template
- Open (fixed) aperture
- Patented LumaLevel™ mounting/leveling system
- Machined aluminum housing, cast base
- Stainless steel hardware
- UL / cUL listed
- Three (3) year warranty



SAMPLE NUMBER: 1900-OA-24-MH39PAR20-120-BK

MODEL	SIZE	SOURCE	VOLTS	FINISH	OPTIONS
1900-OA Open aperture	24	<i>Metal Halide</i> MH39PAR20 39W / PAR20 / medium <i>Includes integral core & coil ballast. Lamp not included.</i>	120, 208 240, 277 347	<i>Painted</i> BK Black BZ Bronze CS City silver VE Verde WT White	EL Electronic HID ballast (120/277V) in lieu of core & coil IT Integral transformer for 12V MR16 source <i>See "Accessories & Technical Data" section of catalog for remote transformers</i>
	30	<i>Halogen</i> 50MR16 50W / MR16 / GU5.3 <i>12V remote or integral transformer required - not included Lamp not included</i>	120/12 277/12		
<i>To ship anchor bolt/template kit in advance</i> LAB Less anchor bolts & template (order kit separately - 7048PK)					



ASPEN 1900-IL

42W (max)
Compact Fluorescent
Line Voltage

FEATURES

- Includes anchor bolts & template
- Low glare internal lens louver
- Patented LumaLevel™ mounting/leveling system
- Machined aluminum housing, cast base
- Stainless steel hardware
- UL / cUL listed
- Three (3) year warranty



SAMPLE NUMBER: 1900-IL-24-CF42-120-BK

MODEL	SIZE	SOURCE	VOLTS	FINISH	OPTIONS
1900-IL Internal louver	24 30	<i>Compact Fluorescent</i> CF42 26W, 32W, or 42W / triple tube / universal GX24q <i>Includes integral universal electronic ballast (120-277V) Lamp not included</i>	120, 208 240, 277	<i>Painted</i> BK Black BZ Bronze CS City silver VE Verde WT White	<i>To ship anchor bolt/template kit in advance</i> LAB Less anchor bolts & template (order kit separately - 7048PK)

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>