

QUICK SETUP GUIDE: PART 1

Cuisinart®

1½-GALLON CLEANWATER® COUNTERTOP FILTRATION SYSTEM

IMPORTANT!

DO NOT THROW AWAY. Read before operating your new water filtration system. Keep for further reference.

This setup guide is intended to be a supplement to the Instruction Booklet. In order to ensure proper setup, safe operation and optimum performance, please read the entire Instruction Booklet.

You will need a large bowl, a pitcher (or another type of container) and a glass to complete this setup. **Do not plug in unit until ALL steps of SETUP are complete.**

WATER FILTER PREPARATION

1.

Remove filter from packaging. **DO NOT WASH FILTER.**


Press filter firmly to the bottom of an empty bowl sideways. Slowly submerge with cold water to cover by 1" and hold under water for 30 seconds.



2.

Release filter and **let soak for at least 15 minutes.** The filter should be partially submerged and may tilt to one side.


While filter is soaking, remove filter timer from lid and wash lid and both tanks with warm, soapy water. Replace timer.



WATER FILTER INSTALLATION


3.

With Cuisinart® logo facing up, insert filter into upper water tank and push firmly into place.



4.

Place upper water tank on a pitcher (or another type of container) and fill with **cold** water. Let drain for 5 minutes, then discard remaining water.



QUICK SETUP GUIDE: PART 2

WATER DISPENSER SETUP


5.

Place upper tank onto lower tank and cover with lid. Place assembled tanks on base with vertical groove on upper tank facing the back of the unit.



6.

Flip lid open and add **cold** water to FILL line. Continue adding to the FILL line until upper and lower tanks are completely full. This may take 30 – 40 minutes.



7.

Place a glass under right spigot and press and hold **COLD** button until water flow is steady. Repeat for **ROOM**. This may take a couple of minutes per button.



8.

Flip lid open and refill upper tank with cold water to FILL line. Continue adding to the FILL line until upper and lower tanks are completely full.



9.

Peel sticker off filter timer and press and hold **START** button until "Filtering" is displayed.



10.

Refer to Instruction Booklet for Operating Instructions.



Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>